

Material Sourcing Gaps - China 2021

Commodity	Material No.	Short Description	Short Description (in Chinese) 产品中文简述 仅供参考	Long Description	Gap ID
Chemicals	6000016483	MUD SYSTEM	高压井泥浆体系	ADMIXTURE DRILLING MUD; ANY, DRILLING FLUIDS SYSTEM OR PRODUCT USED AS WATER BASED MUD(WBM) OR OIL BASED MUD (OBM) OR FOR SPECIAL APPLICATION TO DRILL THE RESERVOIR OR NON-RESERVOIR HOLE SECTIONS. EXAMPLES NON-CONVENTIONAL LCM, HIGH OVER BALANCE MUD SYSTEM, SHALE INHIBITION MUD SYSTEM, RESERVOIR DRILL-IN FLUID(RDF), FILTER CAKE REMOVAL SYSTEM, HIGH PERFORMANCE WATER BASE MUD (HPWBM), HIGH PERFORMANCE OIL BASE MUD (HPOBM), SPACER CLEANING SYSTEM	12126
Chemicals	6000016483	MUD SYSTEM	高温非常规深井泥浆体系	ADMIXTURE DRILLING MUD; ANY, DRILLING FLUIDS SYSTEM OR PRODUCT USED AS WATER BASED MUD(WBM) OR OIL BASED MUD (OBM) OR FOR SPECIAL APPLICATION TO DRILL THE RESERVOIR OR NON-RESERVOIR HOLE SECTIONS. EXAMPLES NON-CONVENTIONAL LCM, HIGH OVER BALANCE MUD SYSTEM, SHALE INHIBITION MUD SYSTEM, RESERVOIR DRILL-IN FLUID(RDF), FILTER CAKE REMOVAL SYSTEM, HIGH PERFORMANCE WATER BASE MUD (HPWBM), HIGH PERFORMANCE OIL BASE MUD (HPOBM), SPACER CLEANING SYSTEM	12127
Chemicals	6000016483	MUD SYSTEM	非常规堵漏材料 LCM	ADMIXTURE DRILLING MUD; ANY, DRILLING FLUIDS SYSTEM OR PRODUCT USED AS WATER BASED MUD(WBM) OR OIL BASED MUD (OBM) OR FOR SPECIAL APPLICATION TO DRILL THE RESERVOIR OR NON-RESERVOIR HOLE SECTIONS. EXAMPLES NON-CONVENTIONAL LCM, HIGH OVER BALANCE MUD SYSTEM, SHALE INHIBITION MUD SYSTEM, RESERVOIR DRILL-IN FLUID(RDF), FILTER CAKE REMOVAL SYSTEM, HIGH PERFORMANCE WATER BASE MUD (HPWBM), HIGH PERFORMANCE OIL BASE MUD (HPOBM), SPACER CLEANING SYSTEM	12128
Chemicals	6000016483	MUD SYSTEM	卤水泥浆体系	ADMIXTURE DRILLING MUD; ANY, DRILLING FLUIDS SYSTEM OR PRODUCT USED AS WATER BASED MUD(WBM) OR OIL BASED MUD (OBM) OR FOR SPECIAL APPLICATION TO DRILL THE RESERVOIR OR NON-RESERVOIR HOLE SECTIONS. EXAMPLES NON-CONVENTIONAL LCM, HIGH OVER BALANCE MUD SYSTEM, SHALE INHIBITION MUD SYSTEM, RESERVOIR DRILL-IN FLUID(RDF), FILTER CAKE REMOVAL SYSTEM, HIGH PERFORMANCE WATER BASE MUD (HPWBM), HIGH PERFORMANCE OIL BASE MUD (HPOBM), SPACER CLEANING SYSTEM	12129
Chemicals	6000016483	MUD SYSTEM	水基泥浆体系	ADMIXTURE DRILLING MUD; ANY, DRILLING FLUIDS SYSTEM OR PRODUCT USED AS WATER BASED MUD(WBM) OR OIL BASED MUD (OBM) OR FOR SPECIAL APPLICATION TO DRILL THE RESERVOIR OR NON-RESERVOIR HOLE SECTIONS. EXAMPLES NON-CONVENTIONAL LCM, HIGH OVER BALANCE MUD SYSTEM, SHALE INHIBITION MUD SYSTEM, RESERVOIR DRILL-IN FLUID(RDF), FILTER CAKE REMOVAL SYSTEM, HIGH PERFORMANCE WATER BASE MUD (HPWBM), HIGH PERFORMANCE OIL BASE MUD (HPOBM), SPACER CLEANING SYSTEM	12130
Chemicals	6000016483	MUD SYSTEM	合成石墨堵漏材料	ADMIXTURE DRILLING MUD; ANY, DRILLING FLUIDS SYSTEM OR PRODUCT USED AS WATER BASED MUD(WBM) OR OIL BASED MUD (OBM) OR FOR SPECIAL APPLICATION TO DRILL THE RESERVOIR OR NON-RESERVOIR HOLE SECTIONS. EXAMPLES NON-CONVENTIONAL LCM, HIGH OVER BALANCE MUD SYSTEM, SHALE INHIBITION MUD SYSTEM, RESERVOIR DRILL-IN FLUID(RDF), FILTER CAKE REMOVAL SYSTEM, HIGH PERFORMANCE WATER BASE MUD (HPWBM), HIGH PERFORMANCE OIL BASE MUD (HPOBM), SPACER CLEANING SYSTEM	12131
Chemicals	6000016483	MUD SYSTEM	任何新型泥浆体系	ADMIXTURE DRILLING MUD; ANY, DRILLING FLUIDS SYSTEM OR PRODUCT USED AS WATER BASED MUD(WBM) OR OIL BASED MUD (OBM) OR FOR SPECIAL APPLICATION TO DRILL THE RESERVOIR OR NON-RESERVOIR HOLE SECTIONS. EXAMPLES NON-CONVENTIONAL LCM, HIGH OVER BALANCE MUD SYSTEM, SHALE INHIBITION MUD SYSTEM, RESERVOIR DRILL-IN FLUID(RDF), FILTER CAKE REMOVAL SYSTEM, HIGH PERFORMANCE WATER BASE MUD (HPWBM), HIGH PERFORMANCE OIL BASE MUD (HPOBM), SPACER CLEANING SYSTEM	12132
Chemicals	1000885304	LUBRICANT OBM	酯基润滑剂	LUBRICANT FOR OBM ESTER-BASED LUBRICANT; LIQUID FORM, 55 GAL (208 LITER) DRUM SHIPMENT OF PRODUCT SHALL CONFORM TO SAUDI ARAMCO EXPORT PACKING MANUAL, ASTM D-92 FOR FLASH POINT, SERVICE: USED TO IMPROVE LUBRICITY OF OIL-BASED MUD SYSTEMS, COMPOSITION: BLEND OF POLYMERIC FATTY ACID ESTERS AND ESTERS, LUBRICANT FOR OBM-ESTER BASED: LIQUID BLEND OF POLYMERIC FATTY ACID ESTER AND ESTER, USED TO IMPROVE LUBRICITY OF OIL-BASED MUD SYSTEMS. IT REDUCES TORQUE AND DRAG, AND THE RISK OF DIFFERENTIAL STICKING IN DEEP, TORTUOUS, HIGH ANGLE OR EXTENDED REACH WELLS. CHEMICAL AND PHYSICAL SPECIFICATIONS: APPEARANCE: YELLOW TO AMBER-YELLOWISH BROWN LIQUID INSOLUBLE IN WATER COMPATIBLE WITH NITRILE ELASTOMERS FLASH POINT (CMOC): >428°F (220°C). SAUDI ARAMCO RESERVES THE RIGHT TO COLLECT REPRESENTATIVE PRODUCT SAMPLES AND CONDUCT LABORATORY TESTS TO ENSURE COMPLIANCE WITH THE MATERIAL DESCRIPTION AND SPECIFICATIONS. PRODUCT MANUFACTURER AND OR SUPPLIER ARE REQUIRED TO SUBMIT LAB CERTIFICATE OF ANALYSIS FOR EVERY BATCH (COA) AND CERTIFICATE OF ORIGIN (COO). LABEL: PRODUCT NAME, BATCH NUMBER, PRODUCTION DATE, EXPIRATION DATE, SAP NUMBER AND COUNTRY OF ORIGIN, MANUFACTURER NAME AND CONTACT INFORMATION. HAZCOM ACCORDING TO THE MATERIAL SAFETY DATA SHEET (MSDS). UOM REFERRED IN THIS MATERIAL IS NET VOLUME/WEIGHT.	12175
Chemicals	1000823699	THINNER OBM	磺酸盐脂肪酸类降黏剂	THINNER/DISPERSANT-OBM CONDITIONER ADDITIVE DRILLING FLUID; LIQUID FORM, SULFONATE BLEND WITH FATTY ACID, FOR USED TO LOWER REHEOLOGICAL PROPERTIES OF OIL BASE FLUIDS. POLYOLEFIN/ORGANIC SULFONATE BLEND WITH FATTY ACID, 55 GALLON (208 LITER) DRUM. SHIPMENT OF PRODUCTS MUST CONFORM TO SAUDI ARAMCO EXPORT PACKING MANUAL, THINNER/DISPERSANT-OIL-BASE MUD CONDITIONER: LIQUID POLYOLEFIN/ORGANIC SULFONATE BLEND WITH FATTY ACID DERIVATIVES USED TO LOWER RHEOLOGICAL PROPERTIES FOR OIL BASE FLUIDS. OTHER ASSOCIATED ELEMENTS MUST NOT BE HARMFUL TO PERSONNEL AND/OR ADVERSELY AFFECT FLUID PROPERTIES. CHEMICAL AND PHYSICAL SPECIFICATIONS: APPEARANCE: DARK AMBER LIQUID SOLUBILITY: INSOLUBLE IN WATER SPECIFIC GRAVITY: 0.90 - 0.96 FLASH POINT (PMCC): > 212°F (100°C) SAUDI ARAMCO RESERVES THE RIGHT TO COLLECT REPRESENTATIVE PRODUCT SAMPLES AND CONDUCT LABORATORY TESTS TO ENSURE COMPLIANCE WITH THE MATERIAL DESCRIPTION AND SPECIFICATIONS. PRODUCT MANUFACTURER AND OR SUPPLIER ARE REQUIRED TO SUBMIT LAB CERTIFICATE OF ANALYSIS FOR EVERY BATCH (COA) AND CERTIFICATE OF ORIGIN (COO). LABEL: PRODUCT NAME, BATCH NUMBER, PRODUCTION DATE, EXPIRATION DATE, SAP NUMBER AND COUNTRY OF ORIGIN, MANUFACTURER NAME AND CONTACT INFORMATION. HAZCOM ACCORDING TO THE MATERIAL SAFETY DATA SHEET (MSDS). UOM REFERRED IN THIS MATERIAL IS NET VOLUME/WEIGHT	12185

Material Sourcing Gaps - China 2021

Chemicals	1000827162	LIGNITE	褐煤	LIGNITE-FILTRATION CONTROL AGENT ADDITIVE DRILLING FLUID; POWDER FORM,LIGNITE, FOR USED FOR FILTRATION AND RHEOLOGY CONTROL OF WATER-BASED MUD,BLACK POWDER NATURALLY OCCURRING LIGNITE,50 LBS. (22.7 KG) BAG. SHIPMENT OF PRODUCTS MUST CONFORM TO SAUDI ARAMCO EXPORT PACKING MANUAL,LIGNITE FILTRATION CONTROL AGENT: BLACK POWDER NATURALLY OCCURRING LIGNITE USED FOR FILTRATION AND RHEOLOGY CONTROL OF WATER-BASED DRILLING FLUIDS. IT FUNCTIONS WELL IN HIGH PH ENVIRONMENTS AND IS TOLERANT OF COMMON MUD CONTAMINANTS SUCH AS CALCIUM UP TO 1000 PPM. IT IS SUITABLE FOR USE IN LIME AND GYPSUM MUD SYSTEMS AT TEMPERATURES EXCEEDING 400°F (204°C). OTHER ASSOCIATED ELEMENTS MUST NOT BE HARMFUL TO PERSONNEL AND/OR ADVERSELY AFFECT FLUID PROPERTIES. CHEMICAL AND PHYSICAL SPECIFICATIONS: APPEARANCE: BLACK POWDER SOLUBILITY: REQUIRES AN ALKALINE WATER TO SOLUBILIZE. PH 9.0 OR ABOVE SPECIFIC GRAVITY @68°F (20°C): 1.6 - 1.8 BULK DENSITY @ 20°C: 40 - 52 LBS/FT3 CRYSTALLINE SILICA, QUARTZ (SiO2): 5%WT. MAXIMUM SAUDI ARAMCO RESERVES THE RIGHT TO COLLECT REPRESENTATIVE PRODUCT SAMPLES AND CONDUCT LABORATORY TESTS TO ENSURE COMPLIANCE WITH THE MATERIAL DESCRIPTION AND SPECIFICATIONS. PRODUCT MANUFACTURER AND/OR SUPPLIER ARE REQUIRED TO SUBMIT LAB CERTIFICATE OF ANALYSIS (COA) AND CERTIFICATE OF ORIGIN (COO) FOR EVERY BATCH. LABEL: PRODUCT NAME, BATCH NUMBER, PRODUCTION DATE, SAP NUMBER, EXPIRATION DATE, AND COUNTRY OF ORIGIN, MANUFACTURER NAME AND CONTACT INFORMATION. HAZCOM ACCORDING TO THE MATERIAL SAFETY DATA SHEET (MSDS). UOM REFERRED IN THIS MATERIAL IS NET VOLUME/WEIGHT.	12204
Chemicals	1001071292	ADDITIVE DRILLING FLUID, LIQUID NON-EMUL	非乳化剂类表面活性剂	NON-EMULSIFIER SURFACTANT. ADDITIVE DRILLING FLUID; LIQUID NON-EMULSIFIER SURFACTANT FORM,NON-EMULSIFIER SURFACTANT, FOR LIQUID FORM, SURFACTANT DESIGNED AS NONEMULSIFIER ADDITIVE FOR ACIDIZING LIMESTONE,DOLOMITE AND SANDSTONE, OR FOR FRACTURE CLEANING TREATMENT LIQUID NON-IONIC WATER DISPERSING NON-EMULSIFIER SURFACTANT DESIGNED FOR APPLICATIONS IN CEMENTING, ACIDICING, WELL STIMATION, AND FRACTURING. THE PRODUCT CAN ALSO BE USED AS TREATMENT OF THE WELLBORE BEFORE DISPLACEMENT FROM OIL BASED MUDS TO WATER BASE,NON-EMULSIFIER SURFACTANT,5 GAL PAIL, NET PRODUCT VOLUME OF 5 GAL,APPEARANCE: YELLOW LIQUID. SPECIFIC GRAVITY AT 68 DEG.F (20 DEG. C): 0.85-0.95. FLASH POINT: >86 DEG. F (30 DEG. C). NON-DEGRADABLE IN 15% HCL. 5 GAL PAIL(18.9 LITERS), NET PRODUCT VOLUME OF 5 GAL. SAUDI ARAMCO RESERVES THE RIGHT TO COLLECT REPRESENTATIVE PRODUCT SAMPLES AND CONDUCT LABORATORY TESTS TO ENSURE COMPLIANCE WITH THE MATERIAL DESCRIPTION AND SPECIFICATIONS. PRODUCT MANUFACTURER AND OR SUPPLIER ARE REQUIRED TO SUBMIT LAB CERTIFICATE OF ANALYSIS FOR EVERY BATCH (COA) AND CERTIFICATE OF ORIGIN (COO). PRODUCT MANUFACTURER AND/OR SUPPLIER ARE REQUIRED TO SUBMIT LAB CERTIFICATE OF ANALYSIS (COA) AND CERTIFICATE OF ORIGIN (COO) FOR EVERY BATCH. UOM REFERRED IN THIS MATERIAL IS NET VOLUME/WEIGHT. LABEL: PRODUCT NAME, BATCH NUMBER, PRODUCTION DATE, SAP NUMBER, EXPIRATION DATE, AND COUNTRY OF ORIGIN, MANUFACTURER NAME AND CONTACT INFORMATION. HAZCOM ACCORDING TO THE MATERIAL SAFETY DATA SHEET MSDS. UOM REFERRED IN THIS MATERIAL IS NET VOLUME/WEIGHT.	12214
Chemicals	1000814796	ACETIC ACID > 96%	醋酸 (纯度大于96%)	MICRO WASH-GLACIAL ACID-BAKER HUGHES ADDITIVE DRILLING FLUID; CLEAR, COLORLESS LIQUID FORM,LIQUID CARBOXYLIC ACID, FOR USED FOR ACIDIZING SOLUBLE CALCIUM CARBONATE PARTICLES AFTER USING OBM.,LIQUID CARBOXYLIC ACID WITH THE MOLECULAR FORMULA OF CH3COOH,275 GALLON IBC TOTE CONTAINER SPECIFICATIONS: LEAK PREVENTION MECHANISM: VALVE CLOSED WITH SCREW CAP PE-DISC AND FLAT GASKET, VALVE HANLDE SECURED WITH A LOCKING SCREW. INNER CONTAINER SHOULD BE HIGH MOLECULAR WEIGHT, HIGH DENSITY POLYETHYLENE (HMWHDPE) W/EXTRUSION BLOW MOLDED, SPECIALLY SHAPED TO ENSURE COMPLETE DISCHARGE OF CONTENTS. OUTER CONTAINER SHOULD BE RIGID, WELDED GALVANIZED TUBULAR STEEL GRID WITH A LARGE PERMANENTLY FIXED IDENTIFICATION PLATE.MOLDED BOTTOM SHELL SHOULD BE PRESSED GALVANIZED STEEL BASE SHAPED TO SUPPORT THE INNER CONTAINER AND ASSIST TOTAL DRAINAGE. PALLETS SHOULD BE STEEL AND HAVE 4 WAYS ENTRIES. SHIPMENT OF PRODUCTS MUST CONFORM TO SAUDI ARAMCO EXPORT PACKING MANUAL.,MICRO-WASH ACETIC ACID-BAKER HUGHES: CLEAR LIQUID CARBOXYLIC ACIDS WITH THE FORMULA OF CH3COOH, USED FOR ACIDIZING SOLUBLE CALCIUM CARBONATE PARTICLES, AFTER USING OBM, IN WELLBORE REMEDIATION AND CLEANUP PROCESS TO IMPROVE WELL PRODUCTIVITY. BAKER HUGHES MICRO-WASH ACID SYSTEM CONSISTS OF: PRIME-743 (SAP #1000811425), PRIME-760 (SAP #1000811426), PRIME-770 (SAP #1000811427), OHR-759 (SAP #1000811421), OHR-AC (SAP #1000811422), OHR-757 (SAP#1000811423), OHR-750 (SAP #1000811424), GLACIAL ACETIC ACID (SAP #1000814796), AND FORMIC ACID (SAP #1000811877). CHEMICAL AND PHYSICAL SPECIFICATIONS: APPEARANCE: CLEAR LIQUID, STRONG PUNGENT VINEGAR ODOR ACETIC ACID: >96% DENSITY: 1040-1050 KG/M³ (1.040-1.050 G/CM³) AT 25°C BOILING POINT: 242.6 °F (117 °C) MINIMUM FLASH POINT: >39 °C/102 °F (CLOSED CLIP) AUTO-IGNITION TEMPERATURE: 799°C. SAUDI ARAMCO RESERVES THE RIGHT TO COLLECT REPRESENTATIVE PRODUCT SAMPLES AND CONDUCT LABORATORY TESTS TO ENSURE COMPLIANCE	12224
Chemicals	1001047513	COPOLYMER LATEX	共聚物胶乳类 (密度: 1.09G/CC)	COPOLYMER LATEX ADDITIVE DRILLING FLUID; LIQUID FORM,COPOLYMER LATEX, FOR ORGANIC COLLOIDAL MICRO-PARTICLES, DEFORMABLE AND COMPRESSIBLE, FOR SEALING MICRO-FRACTURES AND MINIMIZE DIFFERENTIAL STICKING AND TO IMPROVE WELLBORE STABILITY., COPOLYMER LATEX WITH ORGANIC COLLOIDAL MICRO-PARTICLES 208 LITERS, NET VOLUME PLASTIC DRUM. SHIPMENT OF PRODUCTS MUST CONFORM TO SAUDI ARAMCO EXPORT PACKING MANUAL., ORGANIC COLLOIDAL MICRO-PARTICLES, DEFORMABLE, COMPRESSIBLE, FOR SEALING MICRO-FRACTURES AND MINIMIZE DIFFERENTIAL STICKING AND TO IMPROVE WELLBORE STABILITY. IT IS HIGH TOLERANT TO SALTS AND MONOVALENT AND DIVALENT IONS, CAN IMPART FLUIDS LOSS CONTROL, IT DOES PLUG PORES TO REDUCE PERMEABILITY OF FILTER CAKE AND OVERTIME IT FORMS A FILM IN THE FILTER CAKE AT HIGH TEMPERATURES FOR STRENGTHENING THE WELLBORE.IT IS USED IN HIGH PERFORMANCE WATER-BASED MUD (FRESH OR SALT WATER) AT BOTTOM HOLE TEMPERATURES UP TO 450 °F (232 °C). IT IS AN ALTERNATIVE FOR POROSEAL FROM MI SWACO (SAP NO. 1000875825). CHEMICAL AND PHYSICAL SPECIFICATIONS: SPECIFIC GRAVITY: 1.09(G/CC) PH: 5.0-8.0. SAUDI ARAMCO RESERVES THE RIGHT TO COLLECT REPRESENTATIVE PRODUCT SAMPLES AND CONDUCT LABORATORY TESTS TO ENSURE COMPLIANCE WITH THE MATERIAL DESCRIPTION AND SPECIFICATIONS. PRODUCT MANUFACTURER AND OR SUPPLIER ARE REQUIRED TO SUBMIT LAB CERTIFICATE OF ANALYSIS FOR EVERY BATCH (COA) AND CERTIFICATE OF ORIGIN (COO). LABEL: PRODUCT NAME, BATCH NUMBER, PRODUCTION DATE, EXPIRATION DATE, SAP NUMBER AND COUNTRY OF ORIGIN, MANUFACTURER NAME AND CONTACT INFORMATION. HAZCOM ACCORDING TO THE MATERIAL SAFETY DATA SHEET(MSDS). UOM REFERRED	12234

Material Sourcing Gaps - China 2021

Chemicals	1001038020	COPOLYMER LATEX	共聚物胶乳类 (密度: 1.01-1.02G/CC)	COPOLYMER LATEX ADDITIVE DRILLING FLUID; LIQUID FORM,COPOLYMER LATEX,COPOLYMER LATEX WITH ORGANIC COLLOIDAL MICRO-PARTICLES,208 LITERS PLASTIC DRUM. SHIPMENT OF PRODUCTS MUST CONFORM TO SAUDI ARAMCO EXPORT PACKING MANUAL,ORGANIC COLLOIDAL MICRO-PARTICLES, DEFORMABLE,COMPRESSIBLE, FOR SEALING MICRO-FRACTURES AND MINIMIZE DIFFERENTIAL STICKING AND TO IMPROVE WELLBORE STABILITY. IT IS HIGH TOLERANT TO SALTS AND MONOVALENT AND DIVALENT IONS. CAN IMPART FLUIDS LOSS CONTROL. IT DOES PLUG PORES TO REDUCE PERMEABILITY OF FILTER CAKE AND OVERTIME IT FORMS A FILM IN THE FILTER CAKE AT HIGH TEMPERATURES FOR STRENGTHENING THE WELLBORE. IT IS USED IN HIGH PERFORMANCE WATER-BASED MUD (FRESH OR SALT WATER) AT BOTTOM HOLE TEMPERATURES UP TO 320 °F (160 °C). IT IS AN ALTERNATIVE FOR MAXSHIELD FROM BAKER HUGHES (SAP NO. 1000758663). CHEMICAL AND PHYSICAL SPECIFICATIONS: SPECIFIC GRAVITY @ 68 DEG F (20 DEG C): 1.01 – 1.02. (G/CC) PH: 3.6-7.5 SAUDI ARAMCO RESERVES THE RIGHT TO COLLECT REPRESENTATIVE PRODUCT SAMPLES AND CONDUCT LABORATORY TESTS TO ENSURE COMPLIANCE WITH THE MATERIAL DESCRIPTION AND SPECIFICATIONS. PRODUCT MANUFACTURER AND OR SUPPLIER ARE REQUIRED TO SUBMIT LAB CERTIFICATE OF ANALYSIS FOR EVERY BATCH (COA) AND CERTIFICATE OF ORIGIN (COO). LABEL:PRODUCT NAME, BATCH NUMBER, PRODUCTION DATE, EXPIRATION DATE, SAP NUMBER AND COUNTRY OF ORIGIN, MANUFACTURER NAME AND CONTACT INFORMATION. HAZCOM ACCORDING TO THE MATERIAL SAFETY DATA SHEET (MSDS). "UOM REFERRED IN THIS MATERIAL IS NET VOLUME/WEIGHT.	12244
Chemicals	600003963	Aluminum Stearate and/or Silicon base defoamer	硬脂酸铝/硅基消泡剂	CHEMICAL; ANY,MATERIALS USED TO RECING FOAMING IN WATER BASED MUD AND BRINE	12254
Chemicals	600003953	Anhydrous Calcium Bromide Dry	高比重完井液	CHEMICAL; ANY,MATERIALS USED TO INCREASE THE SALINITY AND/OR DENSITY IN WATER BASED MUD, OIL BASED MUD AND BRINE. USED IN COMPLETIONS FLUIDS	12264
Chemicals	1000892841	CHEMICAL, POTASSIUM CARBONATE (K2CO3) 50	碳酸钾50%水合液	CHEMICAL; POTASSIUM CARBONATE (K2CO3) 50% SOLUTION IN WATER,FOR USED AS AN ABSORBANT MEDIA IN GASEOUS PHASE PROCESS SYSTEMS,LIQUID FORM,BULK,POTASSIUM CARBONATE AND WATER,POTASSIUM CARBONATE (K2CO3) 50% SOLUTION IN WATER,POTASSIUM CARBONATE (K2CO3) 50% SOLUTION IN WATER IS USED AS AN ABSORBANT MEDIA IN GASEOUS PHASE PROCESS SYSTEMS	12429
Chemicals	1000178625	ADDITIVE: FUEL OIL, COLD FLOW FUEL	燃料油除蜡添加剂	ADDITIVE: FUEL OIL TYPE,FOR COLD FLOW FUEL ADDITIVE,LIQUID FORM,BULK DELIVERY (20000 KG PER ISOTANK), ASHLESS POLYMERS DISSOLVED IN PETROLEUM DERIVED SOLVENT, ADDITIVE IS USED FOR MODIFYING WAX CRYSTALS IN FUELS TO REACH A DESIRED COLD TEST SPECIFICATIONS (CFPP). TREATMENT RATES RANGE BETWEEN 50 TO 500 PPM DEPENDING ON FUEL CHARACTERISTIC, FLASH POINT (PMC-B), 67 DEG. C	12439
Chemicals	1000184546	CHEMICAL: GR TECHNICAL, METHYL	甲醇	CHEMICAL; GR TECHNICAL,METHYL ALCOHOL,FOR INDUSTRIAL,LIQUID FORM,BULK DELIVERY,SYNTHETIC,METHANOL (WOOD ALCOHOL),ASTM D1152,FED SPEC O-M-232G GRADE A, UN 1230,REQUIRES SAUDI ARAMCO HAZCOM LABEL IN MM# 1000642494	12449
Chemicals	1000959459	CHEMICAL, GT GRADE, METHYLDIETHANOLAMINE	甲基二乙醇胺	CHEMICAL; GR GT GRADE,METHYLDIETHANOLAMINE, FOR GAS TREATMENT AGENT,LIQUID FORM,ISO TANK,2,2-(METHYLIMINO) DIETHANOL N-METHYLDIETHANOLAMINE > 99 %, 2-METHYLAMINOETHANOL N-METHYL-2-ETHANOLAMINE < 0.5%,MDEA,COLORLESS, ODOR: AMMONIACAL, PH: 10.4, BOILING POINT (760 MMHG): 247.3 C, VAPOR PRESSURE < 0.01 KPA AT 20 C, VAPOR DENSITY (AIR = 1): 4.1, SPECIFIC GRAVITY (H2O = 1): 1.041 AT 20 C. MDEA IS CAPABLE OF UNDERGOING REACTIONS TYPICAL OF BOTH ALCOHOLS AND AMINES, FORMING QUATERNARY AMINE SALTS, SOAPS, AND ESTERS. THIS MAKES MDEA A USEFUL INTERMEDIATE IN THE SYNTHESIS OF NUMEROUS PRODUCTS, AND HAS RESULTED IN ITS USE IN MANY DIVERSE AREAS, INCLUDING COATINGS, TEXTILE LUBRICANTS, POLISHES, DETERGENTS, PESTICIDES, PERSONAL CARE PRODUCTS, AND PHARMACEUTICALS.	12458
Chemicals	1000775823	CLAUS CATALYST, TITANIUM DIOXIDE	二氧化钛类克劳斯催化剂	CATALYST; TITANIUM DIOXIDE TYPE,FOR CLAUS SULFUR PLANTS,CYLINDRICAL EXTRUDATE 3-6 MM NOMINAL SIZE FORM,800-1100 KG (1763-2425 LB) SLING BAG, 140-200 KG (308-441 LB) DRUMS,TITANIUM DIOXIDE CLAUS CATALYST MAXIMISES HYDROLYSIS ACTIVITY FOR COS AND CS2, BULK DENSITY, LESS THAN OR EQUAL TO 700 - 1100 KG/M3 (43 - 69 LBS/CU FT), TOTAL PORE VOLUME 0.40 - 0.60 CM3/GRAM, CRUSH STRENGTH MEASURED ON NOT LESS THAN 50 BALLS SHOULD BE GREATER THAN OR EQUAL TO 14 KG , SURFACE AREA 100-260 M2/GRAM, USED IN CLAUS SULFUR REACTORS (CONVERTERS) IN GAS PLANTS & REFINERIES	12469
Chemicals	1000179350	CATALYST: ACTIVATED ALUMINA, CLAUS	活性铝类克劳斯催化剂	CATALYST; ACTIVATED ALUMINA TYPE,FOR CLAUS CATALYST, 3-6 MM, FOR SULFUR REACTOR,SOLID SPHERE FORM,800-1000 KG (1763-2204 LB) SLING BAG,DENSITY LESS THAN OR EQUAL TO 705 K G/CU DENSITY LESS THAN OR EQUAL TO 705 KG/CU M (44LBS/CU FT) REQUIRES SAUDI ARMCO HAZCOM LABEL IN MM# 1000644267	12480
Chemicals	1000179380	CATALYST: ACTIVATED ALUMINA, CLAUS	活性铝类克劳斯催化剂	CATALYST; ACTIVATED ALUMINA TYPE,FOR CLAUS CATALYST,5-10 MM FORM,836.9-918.5 KG (1845-2025 LB) SLING BAG,FOR 1/4 TO 3/8 IN NOM SIZE, BULK DENSITY, LESS THAN OR EQUAL TO 705 KG/CU M (44 LBS/CU FT) MACRO POROSITY GREATER THAN OR EQUAL TO 0.14 CM3/GRAM, CRUSH STRENGTH MEASURED ON NOT LESS THAN 50 BALLS SHOULD BE GREATER THAN OR EQUAL TO 45 LBS' SURFACE AREA GREATER THAN OR EQUAL TO 320 M2/GRAM REQUIRES SAUDI ARAMCO HAZCOM LABEL IN MM# 1000644267	12490
Chemicals	1000183985	CATALYST: CHEMICAL, PROCESS, POWDER,	五氧化二钒类催化剂	CATALYST; CHEMICAL TYPE,FOR PROCESS,POWDER FORM,120 KG/DRUM,COMMON NAME - VANADIUM PENTOXIDE, 99.60% MIN, LOW ALKALI, MELTING POINT 690 DEG C COMPOSITION - A1203-0.006%, CUO-0.005% SPEC PACKING CODE 844405 APPLIES REQUIRES SAUDI ARAMCO HAZCOM LABEL IN MM# 1000644289	12500
Chemicals	6000016190	CATALYST, CHEMICAL, SUPERCLAUS SELECTIVE	克劳斯催化剂	CATALYST; ANY TYPE,CATALYST, CLAUS: FOR SULFUR PLANT AND TAIL GAS TREATING. CONVENTIONAL TYPE NORMALLY ACTIVATED ALUMINA,TITANIA OXIDE OR ALUMINA/TITANIA COMPOSITE TO PROMOTE CLAUS REACTION REACT H2S WITH SO2 TO PRODUCE SULFUR, OR HYDROLYSIS TYPE TO HYDROLYZE COS AND CS2 BACK TO H2S. TGT USED FOR REDUCTION OF TAIL GAS SO2 AND S TO H2S AND HYDROLYZE CS2 AND COS TO H2S USUALLY COBALT-MOLYBDENUM BASED CATALYST.	12511
Chemicals	6000016190	CATALYST, CHEMICAL, SUPERCLAUS SELECTIVE	克劳斯催化剂	CATALYST; ANY TYPE,CATALYST, CLAUS: FOR SULFUR PLANT AND TAIL GAS TREATING. CONVENTIONAL TYPE NORMALLY ACTIVATED ALUMINA, TITANIA OXIDE OR ALUMINA/TITANIA COMPOSITE TO PROMOTE CLAUS REACTION REACT H2S WITH SO2 TO PRODUCE SULFUR, OR HYDROLYSIS TYPE TO HYDROLYZE COS AND CS2 BACK TO H2S. TGT USED FOR REDUCTION OF TAIL GAS SO2 AND S TO H2S AND HYDROLYZE CS2 AND COS TO H2S USUALLY COBALT-MOLYBDENUM BASED CATALYST.	12521
Chemicals	6000001816	SOLVENT, METHYLDIETHANOLAMINE (MDEA)-BAS	硫化氢等酸气吸附剂	ABSORBENT; ANY TYPE,ANY FORM,SOLVENT: FOR GAS AND NGL SWEETENING. INCLUDES CHEMICAL, PHYSICAL, HYBRID GENERIC AMINES OR PROPRIETARY CHEMICALS FOR SELECTIVE OR NON-SELECTIVE REMOVAL OF H2S, CO2, COS,CS2 OR RSH FROM SOUR HYDROCARBON.	12537
Chemicals	6000001816	SOLVENT, METHYLDIETHANOLAMINE (MDEA)-BAS	硫化氢等酸气吸附剂	ABSORBENT; ANY TYPE,ANY FORM,SOLVENT: FOR GAS AND NGL SWEETENING. INCLUDES CHEMICAL, PHYSICAL, HYBRID GENERIC AMINES OR PROPRIETARY CHEMICALS FOR SELECTIVE OR NON-SELECTIVE REMOVAL OF H2S, CO2, COS, CS2 OR RSH FROM SOUR HYDROCARBON.	12538
Chemicals	6000001790	SOLID DESICCANT: DEHYDRATION GAS/LIQ HC	干燥剂	DESICCANT; SOLID DESICCANT TYPE,GR ANY,SOLID DESICCANT: TO REMOVE WATER FROM GAS OR LIQUID HYDROCARBON BY ADSORPTION. USUALLY ALUMINA BASED, MOLECULAR SIEVE, ACTIVATED ALUMINA OR SILICA GEL.	12553

Material Sourcing Gaps - China 2021

Chemicals	6000016171	ADSORBENT: REMOVAL OF Hg, BTEX, HC	除苯类吸附剂	ABSORBENT; ANY TYPE, ANY FORM, ADSORBENT: FOR REMOVAL OF MERCURY, MERCAPTANS, HYDROCARBON (BTEX) OR VOLATILE ORGANIC COMPOUND FROM NATURAL GAS, HYDROCARBON CONDENSATE, LPG, NATURAL GASOLINE AND NAPHTHA AND WATER. IT INCLUDES ACTIVATED CARBON, SULFUR/POTASSIUM IODIDE IMPREGNATED CARBON, METAL SULFIDE OR METAL OXIDE.	12563
Chemicals	6000017151	OIL, HEAT TRANSFER FLUID	导热油	OIL; HEATING TYPE, HEAT TRANSFER FLUID, (HEATING OIL OR HOT OIL), SYNTHETIC OR MINERAL BASE, FOR HYDROCARBON PROCESSING, LOW TEMPERATURE & HIGH TEMPERATURE HEAT TRANSFER FLUID SYSTEMS, USED AS HEAT TRANSFER SYSTEM.	12573
Chemicals	6000003973	Sized metamorphic Marble 2	碳酸钙类堵漏剂	CHEMICAL; ANY, MATERIALS USED TO PREVENT OR CURE LOSS CIRCULATION OR AS BRIDGING MATERIALS IN WATER BASED MUD, OIL BASED MUD AND BRINE.	12583
Chemicals	1000022533	CALCIUM CHLORIDE(77-78%) 1000 KG BIG BAG	氯化钙 (纯度77-78%)	CALCIUM CHLORIDE (77-78%) 1000 KG/BIG BAG ADDITIVE DRILLING FLUID; DRY FLAKES, PELLETS, OR GRANULAR FORM, DRY FLAKES, PELLETS, OR GRANULAR, WATER-SOLUBLE, USED AS WEIGHTING AGENT TO FORMULATE SOLIDS-FREE COMPLETION BRINES AND TO PROVIDE THE DESIRED WATER PHASE SALINITY AND ACTIVITY IN INVERT EMULSION MUDS. IN ADDITION, IT IS USED AS AN ACCELERATOR IN OIL WELL CEMENT SLURRIES. CALCIUM CHLORIDE QUALITY IS MONITORED BY EXPEC ARC LABORATORIES. EXPEC CERTIFICATE OF ACCEPTANCE (EXPEC/COA) REFERRING TO THE RESPECTIVE BATCH NUMBER MUST BE ATTACHED TO EACH SHIPMENT DOCUMENTS ACCEPTED FOR FIELD APPLICATIONS. FOR USED AS WEIGHTING AGENT TO FORMULATE SOLIDS-FREE COMPLETION BRINES AND TO PROVIDE THE DESIRED WATER PHASE SALINITY AND ACTIVITY IN INVERT EMULSION MUDS. IN ADDITION, IT IS USED AS AN ACCELERATOR IN OIL WELL CEMENT SLURRIES. CALCIUM CHLORIDE 77-78%, 1000 KG (2204 LBS) MULTI-WALL MOISTURE-PROOF POLYETHYLENE LINED BAGS WITH LIFTING STRAPS, WITHOUT BOTTOM SPOUT. LIFTING STRAP, BAG IS DISPOSABLE, TOP CLOSURE WATERTIGHT, STACKABLE. MINIMUM TENSILE STRENGTH FACTOR 5, FLEXURAL STRENGTH FOR NORMAL HANDLING AND OUTSIDE STORAGE. THE DISPOSABLE SUPER SACKS SHOULD HAVE AT LEAST 75% OF THEIR SHELF LIFE REMAINING (THE PERIOD FROM DATE OF MANUFACTURING TO THE WARRANTED EXPIRATION DATE) WHEN SHIPPED OR RECEIVED AT DESIGNATED PLACE OF DELIVERY TO SAUDI ARAMCO. REFER TO SAP NUMBER: 1000840600 FOR # DISPOSABLE SUPER SACKS SPECIFICATIONS. SUPPLIERS ARE REQUIRED TO WEIGHT THE TRUCKS BEFORE AND AFTER LOADING AND SUBMIT TO MATERIAL SUPPLY AN OFFICIAL TICKET PRINT DATA STATING: DATE AND TIME, COMPANY AND ADDRESS, TRUCK IDENTITY NUMBER, MATERIAL NAME, TRUCK WEIGHT BEFORE AND AFTER LOADING. SHIPMENT OF PRODUCT SHALL CONFORM TO SAUDI ARAMCO EXPORT PACKING MANUAL, ASTM D98-68/PRACTICE E29 / ASTM D345 - 02(2010) STANDARD TEST METHOD FOR CACL2 SAMPLING AND TESTING, CHEMICAL AND PHYSICAL SPECIFICATIONS APPEARANCE: DRY FREE FLOWING WHITE FLAKES OR PELLETS - PURITY: CACL2 77% WT. MINIMUM PASS THROUGH 7/16 IN SCREEN: 100%WT. NO PARTICLES GREATER THAN 11MM IN ANY DIMENSION. ALKALI CHLORIDES AS NACL: 7% WT. MAXIMUM AND MGCL2: 1% WT. MAXIMUM	N/A
Chemicals	1000022538	CALCIUM CHLORIDE(94-98%) 1000 KG BIG BAG	氯化钙 (纯度94-98%)	CALCIUM CHLORIDE (94-98%) 1000 KG/BIG BAG ADDITIVE DRILLING FLUID; DRY FLAKES, PELLETS, OR GRANULAR FORM, DRY FLAKES, PELLETS, OR GRANULAR, WATER-SOLUBLE USED AS WEIGHTING AGENT FOR FORMULATING SOLIDS-FREE COMPLETION BRINES AND TO PROVIDE THE DESIRED WATER PHASE SALINITY AND ACTIVITY IN INVERT EMULSION MUDS IN ADDITION, IT IS USED AS AN ACCELERATOR IN OIL WELL CEMENT SLURRIES. CALCIUM CHLORIDE QUALITY IS MONITORED BY EXPEC ARC LABORATORIES. EXPEC CERTIFICATE OF ACCEPTANCE (EXPEC/COA) REFERRING TO THE RESPECTIVE BATCH NUMBER MUST BE ATTACHED TO EACH SHIPMENT DOCUMENTS ACCEPTED FOR FIELD APPLICATIONS. FOR USED AS WEIGHTING AGENT FOR FORMULATING SOLIDS-FREE COMPLETION BRINES AND TO PROVIDE THE DESIRED WATER PHASE SALINITY AND ACTIVITY IN INVERT EMULSION MUDS IN ADDITION, IT IS USED AS AN ACCELERATOR IN OIL WELL CEMENT SLURRIES. CALCIUM CHLORIDE 94-98%, 1000 KG (2204 LBS.) MULTI-WALL MOISTURE-PROOF POLYETHYLENE LINED BAGS WITH LIFTING STRAPS, WITHOUT BOTTOM SPOUT. LIFTING STRAP BAG IS DISPOSABLE, TOP CLOSURE WATERTIGHT, STACKABLE. MINIMUM TENSILE STRENGTH FACTOR 5, FLEXURAL STRENGTH FOR NORMAL HANDLING & OUTSIDE STORAGE. THE DISPOSABLE SUPER SACKS SHOULD HAVE AT LEAST 75% OF THEIR SHELF LIFE REMAINING (THE PERIOD FROM DATE OF MANUFACTURING TO THE WARRANTED EXPIRATION DATE) WHEN SHIPPED OR RECEIVED AT DESIGNATED PLACE OF DELIVERY TO SAUDI ARAMCO. REFER TO SAP NUMBER: 1000840600 FOR # DISPOSABLE SUPER SACKS SPECIFICATIONS. SUPPLIERS ARE REQUIRED TO WEIGHT THE TRUCKS BEFORE AND AFTER LOADING AND SUBMIT TO MATERIAL SUPPLY AN OFFICIAL TICKET PRINT DATA STATING: DATE AND TIME, COMPANY AND ADDRESS, TRUCK IDENTITY NUMBER, MATERIAL NAME, TRUCK WEIGHT BEFORE AND AFTER LOADING. SHIPMENT OF PRODUCT SHALL CONFORM TO SAUDI ARAMCO EXPORT PACKING MANUAL, ASTM D98-68/PRACTICE E29 / ASTM D345 - 02 (2010) STANDARD TEST METHOD FOR CACL2 SAMPLING AND TESTING, CHEMICAL AND PHYSICAL SPECIFICATIONS APPEARANCE: DRY FREE FLOWING WHITE FLAKES OR PELLETS - PURITY: CACL2 94 %WT. MINIMUM PASS THROUGH 4 MESH SCREEN: 100%WT. NO PARTICLES GREATER THAN 4.5MM IN ANY DIMENSION ALKALI CHLORIDES AS NACL: 5.0%WT. MAXIMUM - AS MGCL2: 0.5%WT.	N/A
Drilling Equipment	6000004047	Isolation packer expandable	封隔器	PACKER; ANY TYPE, MECHANICAL, SWELLABLE, ISOLATION PACKERS	11949
Drilling Equipment	6000010711	ICD, 4-1/2", NVAM, 12.6#, EQUALIZER CFPLUS	均密器	EQUALIZER; ANY TYPE, EQUALIZER	11525
Drilling Equipment	6000004065	PBR/SEAL, 4-1/2", VTHC, 15.1#, 125KSI, LOWER	封隔器	PACKER PRODUCTION; PERMANENT TYPE, FOR H2S, WIRELINE SET AND HYDRAULIC SET ACTIVATI, ANY OD, ANY CONNECT, KHUFF	11535
Drilling Equipment	6000010715	Tracer Subs system (3-1/2" & 4-1/2")	封隔器	PACKER; ANY TYPE, EQUALIZER, SAND SCREENS, ACCESSORIES, VARIOUS	11545
Drilling Equipment	6000015783	KIT, 7", VALVE+GRV PACKER+SEAL+MFIV	隔离阀和附件	VALVE; ANY TYPE, SIZE ANY ISOLATION VALVES AND ACCESSORIES	11556
Drilling Equipment	6000004055	13 3/8" DV TOOL PHPT 5K Multi stage cementing tools (DV) with "Mechanical non inflatable packer"	分级固井工具 (DV)	COLLAR PACKER; WITH MECHANICAL NON INFLATABLE PACKER TYPE, FOR CEMENTING TOOLS (DV), MULTI STAGE	11966
Drilling Equipment	6000010705	VALVE ICV, 3-1/2", NVAM, 9.2#, 13CR, HCM-A	井下流量控制阀 (ICV) NVAM	ACCESSORY; ANY TYPE, SMART COMPLETION, ACCESSORIES, VARIOUS	11977
Drilling Equipment	0000000000	Wellhead Equipment MSG 6000, 6100, 6200, 6300	井口设备	Wellhead Equipment	11989
Drilling Equipment	6000010715	Tracer Subs system (3-1/2" & 4-1/2")	ICD防砂筛管	PACKER; ANY TYPE, EQUALIZER, SAND SCREENS, ACCESSORIES, VARIOUS	12031
Drilling Equipment	6000010715	Tracer Subs system (3-1/2" & 4-1/2")	ICD	PACKER; ANY TYPE, EQUALIZER, SAND SCREENS, ACCESSORIES, VARIOUS	12032
Drilling Equipment	6000010715	Tracer Subs system (3-1/2" & 4-1/2")	ICD防砂筛管	PACKER; ANY TYPE, EQUALIZER, SAND SCREENS, ACCESSORIES, VARIOUS	12033
Drilling Equipment	6000010715	Tracer Subs system (3-1/2" & 4-1/2")	ICD防砂筛管	PACKER; ANY TYPE, EQUALIZER, SAND SCREENS, ACCESSORIES, VARIOUS	12034
Drilling Equipment	6000010715	Tracer Subs system (3-1/2" & 4-1/2")	ICD防砂筛管	PACKER; ANY TYPE, EQUALIZER, SAND SCREENS, ACCESSORIES, VARIOUS	12035
Drilling Equipment	6000010715	Tracer Subs system (3-1/2" & 4-1/2")	ICD防砂筛管	PACKER; ANY TYPE, EQUALIZER, SAND SCREENS, ACCESSORIES, VARIOUS	12036
Electrical	6000016802	ANODE; MMO GRID, WITHOUT LEAD; CP	MMO网状阳极, 无铅	ANODE IMPRESSED CURRENT; GRID SYSTEM, WITHOUT LEAD TERMINAL, MIXED METAL OXIDE COATED TITANIUM BASE, TITANIUM CONDUCTOR BAR & ANODE WIRE CONNECTION, FOR CATHODIC PROTECTION, 17-SAMSS-007	11032
Electrical	6000015510	ANODE; GALVANIC, HIGH TEMPERATURE ZINC, CP	镀锌阳极, 高温锌	ANODE GALVANIC; HIGH TEMPERATURE ZINC, 17-SAMSS-006, CATHODIC	11041
Electrical	6000015510	ANODE; GALVANIC, HIGH TEMPERATURE ZINC, CP	镀锌阳极, 高温锌	ANODE GALVANIC; HIGH TEMPERATURE ZINC, 17-SAMSS-006, CATHODIC	11042
Electrical	6000012790	ANODE: GALVANIC, MAGNESIUM, CP	阳极, 电镀, 镁	ANODE GALVANIC; MAGNESIUM, 17-SAMSS-006, CATHODIC PROTECTION LARGE SIZE CYLINDRICAL, FOR OFFSHORE APPLICATION	11053
Electrical	6000012080	BOX: JUNCTION, FOR U/G ANODE BED, CP	接线盒, 用于U/G阳极床	BOX ELECTRICAL; CATHODIC PROTECTION UNDERGROUND ANODE BED JUNCTION BOX TYPE, SIZE 2500CM3 (MINIMUM), CYLINDRICAL OR BOX SHAPE, 12X16MM2 AND 2X70MM2 CONNECT, 12-2 TERMINAL SCREW LUG COONNECT, FOR WEATHERPROOF (DIRECT BURIAL), NON-CLASSIFIED, NON-METALLIC SUITABLE FOR DIRECT BURIAL AND IMMERSION SERVICE IN AMBIENT TEMPERATURE SEAWATER, OPTIONAL FINISH, OPTIONAL THK, 17-SAMSS-008 JUNCTION BOX FOR CATHODIC PROTECTION, MEMBRANE GLANDS & FILLER/ SEALING COMPOUND SUITABLE FOR DIRECT BURIAL AND IMMERSION SERVICE IN AMBIENT TEMPERATURE SEAWATE	11062
Electrical	6000001011	POWER SUPPLY, ELECTRICAL, SOLAR, CP	阴极保护电源太阳能充电类型	POWER SUPPLY ELECTRICAL; CATHODIC PROTECTION POWER PLY ELECTRICAL SOLAR POWER TYPE, ANY POWER, ANY, 17-SAMSS-012	11071
Electrical	600000957	CABLE, ELECTRICAL, CP, OFFSHORE ANODE	阴极线, 海上阳极	CABLE ELECTRICAL; ANY SUPPLY, ANY CONDUCTOR, CATHODIC PROTECTION OFFSHORE TYPE, POWER TYPE, 17-SAMSS-017, ARMORED	11082
Electrical	6000001040	ANODE GALVANIC, MAGNESIUM, WITHOUT LEAD, CP	电镀镁阳极, 无铅	ANODE GALVANIC; MAGNESIUM, 17-SAMSS-006, CATHODIC PROTECTION WITHOUT LEADS	11094

Material Sourcing Gaps - China 2021

Electrical	6000015902	UNIT; MOBILE SUBSTATION	移动变电站	UNIT; MOBILE SUBSTATION TYPE,TMSS-01,35-TMSS-1 TMSS-10,46-TMSS-6 TMSS-1,31-TMSS-2 TMSS-2,32-TMSS-3 51-TMSS-1,37-TMSS-1 TMSS-03,11-SDMS-03 54-TMSS-1,MOBILE SUBSTATION AS PER ATTACHED TECHNICAL SPECIFICATION, BASED ON SEC STANDARDS.#SCOPE INCLUDES BUT IS NOT LIMITED TO THE FOLLOWING: ENGINEERING, DESIGN, MANUFACTURING, ASSEMBLING, FACTORY TESTING, DELIVERY TO KSA, MINISTRY OF TRANSPORT APPROVAL, DOCUMENTATION #SPARE PARTS CATALOGUE, SUPPLY OF CRITICAL SPARE PARTS FOR COMMISSIONING, SITE PRE-COMMISSIONING.#	11567
Electrical	6000016594	CAPACITOR BANK	电容器组	UNIT; SHUNT CAPACITOR TYPE, 43-TMSS-01,SAES-P-116,POWER FACTOR CORRECTION CAPACITOR BANK 4.16KV THROUGH 380KV	11577
Electrical	600000919	SWITCHGEAR; LV CONTROLGEAR, FIREWATER PU	开关柜, 低压控制柜, 消防水泵类型	SWITCHGEAR; CONTROLGEAR,FIREWATER PUMP TYPE,ANY BIL,UL-218,LOW VOLTAGE,OUTDOOR	11587
Electrical	600000920	SWITCHGEAR; HV CONTROLGEAR, FIREWATER PU	开关柜, 高压控制柜, 消防水泵类型	SWITCHGEAR; CONTROLGEAR,FIREWATER PUMP TYPE,ANY BIL,UL-218,HIGH VOLTAGE,OUTDOOR	11597
Electrical	600000903	SWITCH; DISCONNECT; HIGH VOLTAGE;	高压隔离开关	SWITCH DISCONNECT; HIGH VOLTAGE,ANY ACTION,ELECTRICAL TYPE,30-TMSS-01	11607
Electrical	6000016991	UNIT; MOBILE SUBSTATION; 69KV AND BELOW	移动变电站, 69KV及以下	UNIT; MOBILE SUBSTATION TYPE,OPERATING AT 69KV AND BELOW	11617
Electrical	6000000774	TRAY; CABLE, FIBERGLASS	玻璃钢桥架	TRAY; CABLE TYPE,FIBERGLASS,NEMA FG-1,S-P-104 SEC. 9	11623
Electrical	6000000841	CIRCUIT BREAKER; AIR; 480 V; LOW VOLTAGE	断路器, 空气开关, 480V低压	CIRCUIT BREAKER AIR; ANY POLE,480 V,LOW VOLTAGE POWER TYPE,FRAME ANY 40 DEG C AMBIENT, FOR INDOOR,16-SAMSS-502	11634
Electrical	6000000999	FORM-WOUND BRUSHLESS SYNCH. MOTOR	无刷同步电机	MOTOR SYNCHRONOUS; 500 HP MINIMUM POWER,4000 V MINIMUM,3 PHASE PHASE HORIZONTAL MTG,17-SAMSS-520	11643
Electrical	6000000803	CABLE,POWER,230 KV,L PRESSURE OIL FILLED	电力电缆, 230KV, 低压力油田使用	CABLE ELECTRICAL HIGH VOLTAGE; HIGH VOLTAGE SUPPLY,ANY CONDUCTO,PIPE OR SELF CONT OIL FILLED TYPE,HIGH MED OR LOW PRESSURE TYPE,AIEC C59	11653
Electrical	6000000929	CABLEBUS 16-SAMSS-520	电缆总线	BUS; SIZE ANY,CABLE,16-SAMSS-520	11663
Electrical	6000003728	PANEL; HYDRAULIC; SSV & SSSV	液压控制面板, SSV&SSSV类型	PANEL; HYDRAULIC, SSV & SSSV TYPE, HYDRAULIC,SSV,SSV,AC APPLICATIONS 34-SAMSS-624,34-SAMSS-630	11673
Electrical	6000000897	PANELBOARD,LOW VOLTAGE, EXPLOSIONPROOF	低压防爆控制柜	PANELBOARD ELECTRICAL; ANY BREAKER,LOW VOLTAGE, EXPLOSIONPROOF TYPE,ANY,16-SAMSS-518	11683
Electrical	6000002328	RACK; SWITCHCRACK;OUTDOOR;LOW VOLTAGE	低压室外开关架	RACK; SWITCHCRACK,OUTDOOR,LOW VOLTAGE TYPE,16-SAMSS-512	11693
Electrical	6000000765	TRANSFORMER; DISTRIBUTION; 60; 30 DEG C	分布式变压器	TRANSFORMER DISTRIBUTION; ANY POWER,60,ANY MTG,40 DEG C MAX AMB,CLASS OA,OIL INSUL,65 DEG C RISE,14-SAMSS-534,OVERHEAD	11703
Electrical	6000011391	RECTIFIER; IMPRESSED CURRENT; 17-SAMSS-0	整流器, 外加电流	RECTIFIER; TYPE CONSTANT VOLTAGE,TAP TYPE,17-SAMSS-004,FOR CATHODIC PROTECTION	11723
Electrical	6000000763	TRANSFORMER, POWER, DRY ABOVE 501 KVA	干式电力变压器, 大于501KVA	TRANSFORMER; ABOVE 501 KVA POWER, HIGH VOLT- DELTA , LOW VOLT - WYE TERMINAL,3 PHASE,60,DRY, POWER TYPE,14-SAMSS-533	11733
Electrical	6000012042	UPS SYS ABOVE 10 TO 200KVA FOR IT & COMM	通信不间断供电电源	POWER SUPPLY UNINTERRUPTIBLE; ABOVE 10 KVA UP TO 200 KVA POWER,17-SAMSS-516,SAES-P-103,MANUFACTURER STANDARD PRODUCT, IT & COMMUNICATION PRODUCT RANGE	11743
Electrical	6000000894	SWITCHGEAR: SF-6, 1 TO 36 KV	SF-6环网柜, 1-36KV	SWITCHGEAR; MANUALLY OPERATED TYPE,1 TO 36 KV,ANY BIL,PAD MTG,16-SAMSS-510,ANSI/IEEE OR IEC,SF-6	12618
Electrical	6000001014	CP,POWER SUPPLY;RECTIFIER;IMPRESSED CURR	整流器外加电流, 阴保供电类型	RECTIFIER IMPRESSED CURRENT; HODIC PROTECTION SE CONTROL TYPE,ANY OUTPUT,17-SAMSS-005	10999
Electrical	6000000761	TRANSFORMER, DISTRIBUTION, PAD MOUNTED	分布式变压器, 座装型	TRANSFORMER DISTRIBUTION; ANY POWER,HV - DELTA, LV - WYE TERMINAL,3 PHASE,5 TAPS,60,PAD MTG,40 DEGREE C MAX AMB,CLASS OA,OIL INSUL,65 DEGREE C RISE,14-SAMSS-536	11111
Electrical	6000000761	TRANSFORMER, DISTRIBUTION, PAD MOUNTED	分布式变压器, 座装型	TRANSFORMER DISTRIBUTION; ANY POWER,HV - DELTA, LV - WYE TERMINAL,3 PHASE,5 TAPS,60,PAD MTG,40 DEGREE C MAX AMB,CLASS OA,OIL INSUL,65 DEGREE C RISE,14-SAMSS-536	11112
Instrumentation and IT	6000002725	ESD; ELECTRONIC; SOLID STATE	固态形式紧急关断系统	RELAY PROTECTION SOLID STATE; ANY COIL,ANY CONTACT,ANY TYPE,EMERGENCY SHUTDOWN SYSTEM ACTION,34-SAMSS-621,SOLID STATE ELECTRONICS BASED USED TO SAFELY SHUTDOWN A PROCESS IN CASE OF PROCESS DEVIATING TO HAZARDOUS OPERATING CONDITIONS.	11713
Instrumentation and IT	6000002786	MONITOR; GAS; HYDROGEN SULFIDE;	硫化氢气体探测器	MONITOR GAS; HYDROGEN SULFIDE ANY RANGE 34-SAMSS-514	11752
Instrumentation and IT	6000001582	CONTROLLER; ELECTRONIC;COMPRESSOR	压缩机控制器	CONTROLLER; COMPRESSOR INCLUDING SURGE CONTROL TYPE,ANY RANGE,SPECIALIZED CONTROL SYSTEMS	11762
Instrumentation and IT	6000002782	MONITOR; GAS; COMBUSTIBLE	可燃气体探测器	MONITOR GAS; COMBUSTIBLE,ANY RANGE,34-SAMSS-514	11773
Instrumentation and IT	6000014614	CUSTODY TANK GAUGING SYSTEM, RADAR	雷达液位 储罐计量系统	GAUGE TANK LEVEL; RADAR CUSTODY TRANSFER TYPE,ANY RANGE,34-SAMSS-321,SAES-Y-301,RADAR TANK GAUGING SYSTEMS FOR CUSTODY TRANSFER	11782
Instrumentation and IT	6000008342	UNIT; REMOTE TERMINAL TYPE	远程终端单元	UNIT; REMOTE TERMINAL TYPE.REMOTE TERMINAL,23-SAMSS-030	11792
Instrumentation and IT	6000009917	CUSTODY SYSTEM, TRUCK LOADING, POS DISP	卸车计量系统	SYSTEM-METERING; CUSTODY TRANSFER METERING TYPE,34-SAMSS-167,TRUCK LOADING, POS DISP, TRUCK LOADING, PD METER, TRUCK LOADING, CORIOLIS METER	11800
Instrumentation and IT	6000002822	GAUGE; RADAR; TANK GAUGING;	雷达液位 储罐计量	GAUGE; RADAR TYPE,ANY RANGE,34-SAMSS-319,TANK GAUGING EQUIPMENT FOR INVENTORY TANK USE ONLY.	11809
Instrumentation and IT	6000009918	CUSTODY SYS TRUCK UNLOADING, POS DISP	卸车计量系统	SYSTEM-METERING; CUSTODY TRANSFER METERING TYPE,34-SAMSS-168,TRUCK UNLOADING, POS DISP	11818
Instrumentation and IT	6000002787	MONITOR; GAS; COMBUSTIBLE; OPEN PATH TYP	开路可燃气体探测器	MONITOR GAS; COMBUSTIBLE,ANY RANGE,34-SAMSS-514,OPEN PATH TYPE	11828
Instrumentation and IT	6000002689	CALIBRATION GAS CYLINDER FOR GAS MONITOR	气体探测器 校验气	CYLINDER; CALIBRATION GAS TYPE,SIZE ANY,ANY,FOR COMBUSTIBLE & TOXIC GAS MONITORS ONLY	11838
Instrumentation and IT	6000002764	INSTRUMENT; LEVEL; RADIATION TYPE	雷达液位计	INSTRUMENT; LEVEL TYPE,LEVEL,RADIATION TYPE	11848
Instrumentation and IT	6000014893	FIBER OPTIC SENSING PLDS	光纤管道泄露监测系统	DETECTOR LEAK; FIBER OPTIC TYPE, FOR PIPELINE,SAES-2-003,THE FIBER OPTIC CABLE SENSING METHOD ANALYSES THE HEAT/TEMP AND THE CONDUCTIVITY OF THE CABLE TO DETECT THE LEAK OCCURS. FOR PIPELINE LEAK DETECTION SYSTEM (PLDS) APPLICATIONS.	11858
Instrumentation and IT	6000012803	VALVE, RELIEF; SURGE PILOT OPERATED	先导式水击泄压阀	VALVE RELIEF; SIZE ANY,ANY END CONN,ANY SUPPLY,ANY,SAES-J-605,SURGE, PILOT OPERATED TYPE , FACTORY TESTING IS REQUIRED FOR COMPLEX RATE-OF-RISE OR MODULATING VALVES.	11868
Instrumentation and IT	6000009906	CUSTODY PRESET CONTROLLER, TRUCK LOADING	卡车装车系统预置控制器	COMPUTER FLOW; CUSTODY PRESET CONTROLLER TYPE,34-SAMSS-847,FOR TRUCK LOADING AND UNLOADING SYSTEMS	11878
Instrumentation and IT	6000001216	CABLE; COMMUNICATIONS; FIBER OPTIC	光纤电缆	CABLE COMMUNICATIONS; ANY CONDUCTO,FIBER OPTIC TYPE,18-SAMSS-625	11888
Instrumentation and IT	6000010821	ACTUATOR: VALVE; ELECTRIC FAILSAFE	失效安全型 电动执行机构	ACTUATOR VALVE ELECTRIC; SIZE ANY,ANY ACTION,34-SAMSS-716,ELECTRIC ACTUATOR FOR OPERATING VALVE, FAILSAFE DESIGN	11898
Instrumentation and IT	6000002914	ANALYZER; GAS CHROMATOGRAPH; Sheltered	气相色谱分析仪	ANALYZER; GAS CHROMATOGRAPH TYPE,ANY RANGE,34-SAMSS-510,PROCESS GAS OR LIQUID	11908
Instrumentation and IT	6000002886	GAUGE; LEVEL; GLASS	玻璃液位表	GAUGE LEVEL; GLASS TYPE,34-SAMSS-010,WITH BACKFLOW PREVENTER VALVE OR CHECK VALVE AS ASSEMBLY IF REQUIRED.	11918
Instrumentation and IT	6000014021	Analyzer; Physical Property	物性分析仪	ANALYZER; PHYSICAL PROPERTY TYPE,ANY RANGE,(EXAMPLE: BOILING POINT, FLASH POINT, POUR POINT, CFPP, RVP, COLOR, CLOUD POINT, FREEZE POINT, OCTANE, AND VISCOSITY)	11927
Instrumentation and IT	6000009890	CUSTODY PROVER, SMALL VOLUME, UNI PISTON	液位计校准仪	METER; UND PISTON(SMALL VOLUM) PROVER TYPE,34-SAMSS-119,FOR LIQUID CUSTODY TRANSFER	11936
Instrumentation and IT	6000009832	CUSTODY METER, POS DISPL , LIQUID	正位积液流量计量	FLOWMETER POSITIVE DISPLACEMENT; CUSTODY TRANSFER LIQUID TYPE,ANY,34-SAMSS-118	11952
Instrumentation and IT	6000009881	Custody Meter, Multi-Path, Ultrasonic Liquid	多通道超声波流量计	FLOWMETER; CUSTODY TRANSFER LIQUID TYPE,CUSTODY TRANSFER LIQUID	12014
Instrumentation and IT	6000009893	CUSTODY AUTOMATIC SAMPLING, LIQUID	自动取样系统	SAMPLER; CUSTODY TRANSFER TYPE,34-SAMSS-525	12054
Instrumentation and IT	6000009895	CUSTODY DENSITY METER, LIQUID	液体密度计	METER DENSITY; CUSTODY TRANSFER LIQUID TYPE,34-SAMSS-510	12076
Instrumentation and IT	6000009898	CUSTODY CHROMATOGRAPH, GAS OR LIQUID	气液色谱	CHROMATOGRAPH PROCESS; FOR CUSTODY TRANSFER CHROMATOGRAPHY,ANY DETECTOR,ANY CARRIER,34-SAMSS-510	12086
Instrumentation and IT	6000013921	ANALYZER, Proc Photometer/Spectrometer	光谱仪	ANALYZER; ANY RANGE,34-SAMSS-515,PROCESS PHOTOMETERS AND SPECTROMETERS INCLUDING TUNABLE DIODE (EXTRACTIVE)	12280
Instrumentation and IT	6000014890	REAL-TIME TRANSIENT MODEL PLDS	实时瞬变管道泄漏监测系统	DETECTOR LEAK; RTTM METHODS TYPE, FOR PIPELINE,SAES-2-003,SYSTEMS USE MATHEMATICAL MODELS OF THE FLOW WITHIN A PIPELINE TO DETECT THE LEAK. FOR PIPELINE LEAK DETECTION SYSTEM (PLDS) APPLICATIONS.	12301
Instrumentation and IT	6000014891	ACOUSTIC PRESSURE WAVES PLDS	声波管道泄漏监测系统	DETECTOR LEAK; NEGATIVE PRESSURE WAVE (ACOUSTIC) TYPE, FOR PIPELINE,SAES-2-003,THE ACOUSTIC PRESSURE WAVE METHOD ANALYSES THE RAREFACTION WAVES PRODUCED WHEN A LEAK OCCURS. FOR PIPELINE LEAK DETECTION SYSTEM (PLDS) APPLICATIONS.	12311

Material Sourcing Gaps - China 2021

Instrumentation and IT	600002732	MONITOR; FLAME MONITORING SYSTEM	火焰监测系统	MONITOR; IGNITERS AND BURNERS USED E MONITORING SYSTEM D IN FIRED EQUIPMENT. TYPE,ANY RANGE,34-SAMSS-617	12321
Instrumentation and IT	600002856	VALVE; AUTOMATIC RECIRCULATION;	自控流量阀	VALVE; AUTOMATIC RECIRCULATION TYPE,SIZE ANY,34-SAMSS-711	12330
Instrumentation and IT	6000010782	CONTROLLER; SMART VALVE POSITION TYPE	智能型定位器	CONTROLLER; SMART VALVE POSITION TYPE,ANY RANGE,34-SAMSS-634,FOR USE WITH EMERGENCY SHUTDOWN VALVES.	12339
Instrumentation and IT	6000009091	CUSTODY FLOW COMPUTER, LIQUID, FIELD-MNT	现场安装型 流量计算机	COMPUTER FLOW; FIELD MOUNTED TYPE,34-SAMSS-841,34-SAMSS-846,FOR LIQUID AND GAS CUSTODY TRANSFER	12349
Instrumentation and IT	600002896	VALVE; RELIEF; SURGE GAS LOADED	气体式水击泄压阀	VALVE RELIEF; SIZE ANY,ANY END CONN,ANY SUPPLY,ANY,SAES-J-605,SURGE GAS LOADED TYPE.	12359
Instrumentation and IT	6000013000	Multiplexer; Foundation Fieldbus (FF)	现场总线多路连接器	MULTIPLEXER; FOUNDATION FIELDBUS (FF) TYPE,SAES-J-904,AA MULTI-INPUT TEMPERATURE	12369
Instrumentation and IT	6000010781	FOUNDATION FIELDBUS (FF) BLOCKS	现场总线模块	BLOCK; FOUNDATION FIELDBUS(FF) WIRING TYPE,INCLUDING POWER SUPPLIES, FOR USE WITH FOUNDATION FIELD-BUS INSTRUMENTS ONLY	12379
Instrumentation and IT	600002720	ANALYZER; DENSITY METER; GAS AND LIQUID	气液密度计分析仪	ANALYZER; DENSITY METER TYPE,ANY RANGE,34-SAMSS-510,GAS AND LIQUID SERVICE	12389
Instrumentation and IT	6000002221	TUBING; INSTRUMENTATION; METALLIC	仪表管	TUBING; INSTRUMENTATION TYPE,STAINLESS STEEL OR NICKEL ALLOYS,ASTM A269,WITH SIZE 3/4 INCH (18 MM) OR SMALLER.	12399
Instrumentation and IT	6000009899	CUSTODY FLOW COMPUTER, LIQUID, PANEL-MNT	面板安装型 流量计算机	COMPUTER FLOW; PANEL MOUNTED TYPE,34-SAMSS-841,FOR LIQUID CUSTODY TRANSFER	12409
Instrumentation and IT	6000009831	CUSTODY METER, TURBINE, LIQUID	液体涡轮流量计	FLOWMETER TURBINE; CUSTODY TRANSFER LIQUID TYPE,ANY,34-SAMSS-17	12419
Others	6000001829	COIL; REFRIGERATION;HVAC USE	盘管; 制冷; 暖通空调用	COIL; COIL, REFRIGERATION, HOT/CHILLED WATER APPLICATIONS TYPE,AHRI 410 CERTIFIED	10883
Others	6000001846	HEATER; DUCT; ELECTRIC;	加热器; 风管; 电加热;	HEATER DUCT; ELECTRIC ELEMENT,ANY	10901
Others	6000001882	AIR CONDITIONING UNIT; DIRECT EXPANSION;	空调机组; 直接膨胀式	AIR CONDITIONING UNIT; DIRECT EXPANSION TYPE,27-SAMSS-002,UL-1995 AHRI-210/240 (< 5.5 TON),AH,HVAC/REFRIGERATION-SYSTEMS FOR PROCESS AND OFFSHORE APPLICATIONS	10928
Others	6000013330	FILTER, AIR, CHEMICAL	过滤器, 空气, 化学	FILTER; ANY TYPE, FOR AIR, CHEMICAL,ISA 571.04,ASTM-D6646 OR ASHRA	10945
Others	6000002419	Water Filter Media	滤水介质	FILTER; SAND BED TYPE, FOR WATER SERVICE, FILTER MEDIA,WATER,32-SAMSS-034,WATER FILTER MEDIA INCLUDING: SAND, ANTHRACITE, MANGANESE GREEN SAND, BERM, GARNET, GRAVEL (AS SUPPORTING LAYER). MERGE WITH 6000001776, 6000001777, 6000002510	10954
Others	6000008724	PRELIMINARY TREATMENT/SW SCREENING SYS	初步处理/海水格栅系统	SCREEN; PRELIMINARY TREATMENT/SEAWATER SCREENING SYSTEMS TYPE,WASTEWATER	10971
Others	6000012705	Oil Skimmer	收油器	UNIT; OIL SKIMMER TYPE,OIL/WATER-OIL SKIMMERS: A DRUM, DISK SURFACE OIL SKIMMER, OR DOUBLE ARM INTERNAL FLOAT OIL SKIMMER THAT REMOVES SURFACE OILS FLOATING ON OILY WATER RELY ONADHESION OF OIL TO THE SURFACE OF THE MECHANISM.	10979
Others	6000008555	Thermal & Electro-dialysis Desal Sys	热电渗析脱盐系统	DESALINATION; THERMAL & ELECTRO-DIALYSIS DESALINATION SYSTEMS TYPE,REVERSAL (EDR) EQUIPMENT	10988
Others	6000001310	HYDRANT FIRE; 5 IN INTEGRATED NOZZLE X 2-1/2 IN NPT (2 EA) MAIN	消防栓; 5英寸集成喷嘴	HYDRANT FIRE; 6 IN INLET,PR 200 PSI WP,UL OR/AND FM,COMPLYING WITH 21-SAMSS-15 WITH OR WITHOUT FIRE MONITOR FLANGE. WITH OR WITHOUT BREAKABLE FLANGE CHECK VALVE ASSEMBLY .FOR BREAKABLE FLANGE VALVE SEPARATELY. PURCHASE ORDER MUST SPECIFY THE OPTIONS AS PER 21-SAMSS-15.	11125
Others	6000001314	MONITOR; FIREFIGHTING, HYDRANT-MOUNTED TYPE,UL/FM	消防炮; 消防, 消防栓上固定型, UL / FM 认证	MONITOR; FIREFIGHTING, HYDRANT-MOUNTED TYPE,ANY RANGE,MEETING 21-SAMSS-16,INDUSTRIAL MONITOR SYSTEM, WILL BE INSTALLED ON#9COM 6000001310	11132
Others	6000001331	BARRIER; FIRE STOPPING; MULTI-CABLE	消火障	BARRIER; FIRE STOPPING TYPE,BARRIERS, MULTI-CABLE TRANSIT SYSTEM INCLUDING PUTTY, MORTAR, PILLOWS, CAULKING, SEALANTS, TAPE, SPRAYS OR OTHER SYSTEMS. MUST COMPLY WITH ANS/UL 1479, ASTM E 814, NFPA/NEC 70, ASTM E 119 AND HAVE MINIMUM F RATING OF 2 HOURS, T RATING OF 1 HOUR, AND MINIMUM L RATING OF LESS THAN 1 HOUR. MUST BE UL/FM LISTED OR APPROVED.	11139
Others	6000014422	MONITOR; FIREFIGHTING, REMOTE CONTROL TYPE,ELECTRICALLY OPERATED	监视器; 消防, 遥控型, 电控	MONITOR; FIREFIGHTING, REMOTE CONTROL TYPE,ANY RANGE,ELECT OR HYDRAULIC OPERATED SUPPLY,MEETING 21-SAMSS-16,FULL SYSTEM FULL CONTROL. INDUSTRIAL APPLICATIONS MEETING PROJECT SPECS	11147
Others	6000002872	VALVE; DIFFERENTIAL DIAPHRAGM TYPE,DELUGE FLOOD	阀门; 差分隔膜膜类型	VALVE; DIFFERENTIAL DIAPHRAGM TYPE,SIZE ANY,DELUGE FLOOD	11155
Others	6000002696	PANEL CONTROL; FIRE PUMP TYPE,UL/FM LISTED/APPROVED,COMPLY	控制面板; 消防泵用, UL / FM 认证	PANEL CONTROL; FIRE PUMP TYPE,UL/FM LISTED/APPROVED,COMPLY W,TYPE,UL-LISTED OR FM APPROVED, PANELS SHALL BE LISTED FOR +50 DEG. CELSIUS, ENCLOSURE MUST BE NEMA 250/NEMA TYPE 4 FOR ONSHORE AND NEMA TYPE 4X FOR OFFSHORE AND NEAR SHORE ENVIRONMENT OUTDOOR WITH SHELTER INSTALLATION, INDOOR WITH AIR-CONDITIONED INSTALLATIONS ARE ALLOWED TO BE ONLY UL/FM APPROVED WITHOUT 50 DEGREES/NEMA 4/4X ENCLOSURE, ALL PANELS MUST BE CAPABLE OF PROVIDING THE PUMPS SEQUENCING FUNCTIONS IN SAES-B-017, CONTACT FRPD RSA FOR DETAILS	11163
Pipe & OCTG	600000409	Hose; High pressure 500 psig and greater	高压软管; 500PSI及以上 SAE100R	HOSE; SIZE ANY, FOR GENERAL PURPOSES,PR HIGH PRESSURE 500 PSIG AND GREATER, REINFORCED NATURAL OR SYNTHETIC RUBBER,SAE 100R,FOR GENERAL PURPOSES SUCH AS OIL AND WATER-BASED FLUIDS, PNEUMATIC APPLICATIONS, LOW PRESSURE HYDRAULIC, LUBRICATING FLUIDS, WATER# ETC.	11192
Pipe & OCTG	6000013160	PIPE&FITTINGS;NON-METAL;RTR	玻璃钢 (RTR) 非金属管&管件	PIPE NON-METALLIC; MAXIMUM 14 IN NPS,REINFORCED THERMOSETTING RESIN,REINFORCED THERMOSETTING RESIN (RTR),FOR WATER (NON-UTILITY) AND HYDROCARBON APPLICATIONS MAX TEMP 200 F,01-SAMSS-042,API 15HR API 15LR	11176
Pipe & OCTG	6000013900	PIPE; NON-METAL; LINED PIPING SYSTEMS	衬氟管道	PIPE NON-METALLIC; SIZES RANGES FROM NPS 1 TO 20 NPS,ASME/ANSI CLASS 150 AND 300 SUPPLY, CARBON STEEL, NGED PIPE&FITTINGS SYSTEM VY DUTY PTFE& PFA LINED,01-SAMSS-025,CORROSIVE FLUIDS INCLUDING ACIDS AND ALKALINE SOLUTIONS SUCH AS HYDROCHLORIC ACID, NITRIC ACID, PHOSPHORIC ACID, CHLORINE/WATER, HYDRAULIC OIL, HYPOCHLORITE (SODIUM OR CALCIUM), SODIUM HYDROXIDE (CAUSTIC SODA), WATER, SEA/SALINE, WATER, AERATED AQUIFER, DESALINATION BRINE, PRODUCED WATER, DISPOSAL SALT, WATER BRINE.	11187
Pipe & OCTG	6000014681	SERVICE: WET -TYPE COMPOSITE REPAIR EXT.	外腐蚀管道复合修复服务; 湿式	SERVICE; WET-TYPE THERMOSET COMPOSITE FIBER REINFORCED COMPOSITE. TYPE,SAEP-345,ASME-PCC2 ISO 24817,USE FOR WATER, HYDROCARBON, CHEMICALS PLANT PIPING AND PIPELINES. SUITABLE FOR EXTERNAL CORROSION UP TO 80 PERCENT METAL LOSS. FOR PLANT PIPING AND FITTINGS, IT SHALL BE UTILIZED AS A TEMPORARY REPAIR WITH A PRIOR APPROVAL FROM NONMETALLIC SCC	11182
Pipe & OCTG	6000015710	SERVICE: WET-TYPE; COMPOSITE REPAIR, INT	内腐蚀管道复合修复服务; 湿式	SERVICE; WET-TYPE THERMOSET COMPOSITE FIBER REINFORCED TYPE,SAEP-345,ASME-PCC2 ISO 24817,USE FOR WATER, HYDROCARBON, CHEMICALS PLANT PIPING AND PIPELINES. SUITABLE FOR INTERNAL CORROSION UP TO 80 PERCENT METAL LOSS PROVIDED THAT CORROSION SOURCE IS MITIGATED. FOR PLANT PIPING AND FITTINGS, IT SHALL BE	11199
Rotating Equipment	6000017500	UNIT, METALLIC 3DPRINTING/ADDITIVE MANUF	金属3D打印/增材制造单元	UNIT; METALLIC 3DPRINTING/ADDITIVE MANUFACTURING INCLUDING ALL TYPE OF STEEL (E.G. INCONEL, TITANIUM, STAINLESS STEEL) TYPE,ANY METALLIC 3D PRINTED PRODUCT INCLUDING NEW PARTS MANUFACTURING, PART MODIFICATION AND REPAIR. METALLIC PART SUCH AS ROTATING EQUIPMENT, STATIC EQUIPMENT AND DRILL EQUIPMENT	11208
Rotating Equipment	6000002244	COMPRESSOR; AIR; CENTRIFUGAL; INTEGRALLY	压缩机; 空气用; 离心式; 整体式	COMPRESSOR AIR; CENTRIFUGAL, INTEGRALLY GEARED TYPE,31-SAMSS-006	11215
Rotating Equipment	6000002351	PUMP; CENT, INLINE, ASMEB73.2 OR ISO5199	泵; 管线离心式, 符合ASMEB73.2或ISO5199	PUMP CENTRIFUGAL; INLINE TYPE,SIZE ANY,ANY,SINGLE STAGE(S),VERTICAL MTG,ASME B73.2 OR ISO 5199	11221
Rotating Equipment	6000002363	PUMP; ROTARY; PROGRESSIVE CAVITY;	回转泵; 渐近空腔式;	PUMP ROTARY; PROGRESSIVE CAVITY TYPE,ANY,API 676	11230
Rotating Equipment	6000002365	PUMP; VACUUM; API 681, HIGH POWER	真空泵; 符合API 681, 高功率	PUMP; VACUUM TYPE,ANY,API 681,HIGH POWER, LIQUID RING VACUUM PUMPS OR COMPRESSORS	11238
Rotating Equipment	6000002371	PUMP; CENTRIFUGAL;VERTICAL;MOLTEN SULFUR	泵; 离心式; 立式; 硫磺熔融输送	PUMP CENTRIFUGAL; VERTICAL TYPE,SIZE ANY,ANY,SINGLE STAGE(S),MFR STD DESIGN +SAES-G-005,MOLTEN SULFUR, SUMP	11246
Rotating Equipment	6000002417	FILTER; ELEMENT; COMBUSTION GAS TURBINE;	过滤器; 过滤原件; 燃气轮机用	FILTER ELEMENT; FOR COMBUSTION GAS TURBINE,32-SAMSS-008,AIN,INLET, FINAL STAGE	11256
Rotating Equipment	6000002453	Mixer; Side Entry; 32-Samss-017; Geared;	混合器; 侧入式; 齿轮传动	MIXER; SIDE ENTRY TYPE 32-SAMSS-017,GEARED, ELECTRIC DRIVEN	11263
Rotating Equipment	6000008842	PUMP, CENTRIFUGAL, HORIZONTAL, MOLTEN SU	泵, 离心式, 卧式, 硫磺熔融输送	PUMP CENTRIFUGAL; HORIZONTAL TYPE,SIZE ANY,ANY,SINGLE STAGE(S),MFR STD DESIGN +SAES-G-005,MOLTEN SULFHUR	11271
Rotating Equipment	6000010363	PUMP; MULTIPHASE, HELICO-AXIAL TYPE,ANY,31-SAMSS-004	泵; 多相, 螺旋轴流式	PUMP; MULTIPHASE, HELICO-AXIAL TYPE,ANY,31-SAMSS-004	11280
Rotating Equipment	6000016780	EJECTOR; PROCESS GAS	喷射器; 工艺气体	EJECTOR; GAS OR LIQUID,ANY PROCESS,ANY,NACE MR-0175/ISO-15156,EJECTOR PACKAGE FOR PROCESS GAS COMPRESSION. NOT FOR STEAM-VACUUM SERVICES.	11289
Static Equipment	6000001821	AIR HANDLING UNIT; AHU; CHILLED WATER OR	空气处理机组; 冷水机组或	AIR HANDLING UNIT; AHU TYPE,CHILLED WATER OR DIRECT EXPANSION,ONSHORE ALL SIZES AND OFFSHORE LESS THAN 10 TONS COOLING,MANUFACTURER STANDARD	10846

Material Sourcing Gaps - China 2021

Static Equipment	600001822	AIR CONDITIONING UNIT; SELF CONTAINED; O	空调机组; 独立式	AIR CONDITIONING UNIT; SELF CONTAINED TYPE,(PACKAGED UNIT) CERTIFIED TO AHRI 340 AND UL 1995 STD	10855
Static Equipment	600001823	AIR CONDITIONING UNIT; PACKAGED UNIT TRA	空调机组; 集装箱式	AIR CONDITIONING UNIT; PACKAGED UNIT TRAILERIZED TYPE,AIR COOLED,R-22 OR R-134A,MANUFACTURER STANDARD	10864
Static Equipment	600001826	A/C Unit,mini-split,DE below 5.5 Tons	空调单元; 小型分体式, 直膨, 低于5.5吨	AIR CONDITIONING UNIT; AIR CONDITIONING UNIT SPLIT TYPE, LESS THAN 5.5 TON COOLING TONNAGE, DIRECT EXPANSION TYPE,AHRI 210/240,UL-1995	10872
Static Equipment	600001862	A/C UNIT;SPLIT;DIRECT EXP,5.5 TO 63 TONS	空调单元; 分体式;直膨, 5.5至63吨	AIR CONDITIONING UNIT; AIR CONDITIONING UNIT SPLIT UNIT DIRECT EXPANSION TYPE,SIZES 5.5 TO 63 COOLING TONNAGE COOLING,AHRI 340/360,UL1995,EER VALUE SHALL BE IN ACCORDANCE WITH THE EER TABLE IN SAES-K-001.	10910
Static Equipment	600001881	AIR CONDITIONING UNIT; AIRCONDIONING AND	空调机组	AIR CONDITIONING UNIT; AIRCONDIONING AND PROCESS REFRIGERATION SYSTEMS TYPE,ONSHORE ALL SIZES, OFFSHORE LESS THAN 10 TONS. COOLING,AHRI-210/240 (< 5.5 TONS),AHRI,EXPLOSION PROOF	10919
Static Equipment	600002404	TOWER; COOLING; WATER;	水冷却塔;	TOWER COOLING; WATER TYPE 27-SAMSS-003,ASHRAE 90.1	10936
Static Equipment	600002515	SKID WATER DISINFECTION SYSTEMS	水消毒系统撬	GENERATOR; WATER DISINFECTION TYPE,HYPOCHLORITE,WATER DISINFECTION SYSTEMS INCLUDING: HYPOCHLORINATION, CHLORINE SYSTEMS, CHLORINE DIOXIDE, BROMINE SYSTEMS, UV SYSTEMS, OZONE SYSTEMS, ANY OTHER DISINFECTING SYSTEMS. MERGE WITH 6000002517.	10962
Static Equipment	600002515	SKID WATER DISINFECTION SYSTEMS	水消毒系统撬	GENERATOR; WATER DISINFECTION TYPE,HYPOCHLORITE,WATER DISINFECTION SYSTEMS INCLUDING: HYPOCHLORINATION, CHLORINE SYSTEMS, CHLORINE DIOXIDE, BROMINE SYSTEMS, UV SYSTEMS, OZONE SYSTEMS, ANY OTHER DISINFECTING SYSTEMS. MERGE WITH 6000002517.	10963
Static Equipment	600000066	TUBING; COPPER-ALLOY; EEMUA; ASTM	管道; 铜合金; 符合EEMUA, ASTM标准	TUBING; ANY TYPE COPPER-ALLOY, INCLUDING COPPER NICKEL (90-10, 70-30, C70600, OR C71500),EEMUA144,ASTMB466 ASTMB111	11297
Static Equipment	600000181	FLANGE; PIPE; COPPER NICKEL, EEMUA 145	法兰 管道用; 铜镍合金, 符合EEMUA 145	FLANGE PIPE; ALL DESIGNS TYPE,ANY NPS,ANY,EEMUA 234,COPPER-ALLOY FLANGES AND CS BACKING (LAP JOINT) FLANGES PER EEMUA 234. OR OTHER COPPER ALLOYS AS PER ASME 16.5, PIPE FLANGES AND FLANGED FITTINGS, UTILITY, NON-HYDROCARBON.	11311
Static Equipment	600000245	VALVE; BALL; TOP ENTRY, RISING STEM	球阀; 顶装式, 加长阀杆	VALVE, BALL; SIZE ALL,ALL SUPPLY,FLANGED OR BUTTWELD END CONN,STEEL BODY,STYLE TOP ENTRY, RISING STEM-,SINGLE, METAL SEATED SEAT,04-SAMSS-035,04-SAMSS-048 SAMSS-051,API-6D,WITH OR WITHOUT ACTUATOR	11318
Static Equipment	600000254	VALVE; BALL; SCRAPER LAUNCHING; STEEL	球阀; 清管器阀	VALVE, BALL; SIZE ANY,ANSI CL 150 AND UP SUPPLY,FLANGED OR BUTTWELD END CONN,STEEL BODY,STYLE SCRAPER LAUNCHING,SOFT SEATED SEAT,04-SAMSS-051,04-SAMSS-035 04-SAMSS-048,WITH OR WITHOUT ACTUATOR	11326
Static Equipment	600000275	VALVE; CHECK;SWING;UP TO 12 IN; CI OR DI	旋启式止回阀; 铸铁 最大12英寸	VALVE CHECK; SIZE UP TO 12 INCH,CAST OR DUCTILE IRON BODY,SWING,FLANGED, LUG OR WAFER END CONN,04-SAMSS-035,04-SAMSS-048 04-SAMSS-005	11335
Static Equipment	600000292	VALVE; GATE; UP TO 12 INCH; NON-FERROUS;	闸阀; 青铜, 铜铝合金, 最大12英寸	VALVE GATE; SIZE UP TO NPS 12,ANY RATING, ALLEND SUPPLY,NON-FERROUS, (BRONZE/ALUMINUM-BRONZE BODY,04-SAMSS-035,04-SAMSS-048 04-SAMSS-001,WITH OR WITHOUT ACTUATOR	11340
Static Equipment	600000296	VALVE; GATE; WEDGE OR DBL DISC; UP TO 12	闸阀; 铸铁 最大12英寸	VALVE GATE; SIZE UP TO NPS 12,ANY RATING, ALLEND SUPPLY,CAST OR DUCTILE IRON BODY,04-SAMSS-035,AWWA,WITH OR WITHOUT ACTUATOR	11344
Static Equipment	600000297	VALVE GATE; SIZE NPS 14 AND ABOVE	闸阀; 铸铁 NPS 14英寸及以上	VALVE GATE; SIZE NPS 14 AND ABOVE,ANY RATING, ALLEND SUPPLY,CAST OR DUCTILE IRON BODY,04-SAMSS-035,AWWA,WITH OR WITHOUT ACTUATOR	11349
Static Equipment	600000315	VALVE; CHOKE; AUTOMATIC PLUG-AND-CAGE; H	节流阀	VALVE CHOKE; PLUG-AND-CAGE SINGLE STAGE TRIM TYPE,UPTO 6 INCH MAXIMUM ORIFICE BODY,PR 10,000 PSI,FLANGED HUBBED OR BUTTWELD END CONN,STEEL BODY,04-SAMSS-055,API 6A,WITH OR WITHOUT ACTUATOR	11354
Static Equipment	600000317	VALVE; PLUG; 4-WAY DIVERTER; 2 THRU 24	旋塞阀; 插头; 4路分流; 2至24英寸	VALVE PLUG; 4-WAY DIVERTER TYPE, SIZE NPS 2 THRU 24,ASME CLASS 150 THRU 600 SUPPLY,FLANGED OR BUTTWELD END CONN,STEEL BODY,04-SAMSS-042,04-SAMSS-035 04-SAMSS-048,WITH OR WITHOUT ACTUATOR	11360
Static Equipment	600002393	BOILER; FIRE TUBE; AND COMONENTS	锅炉; 直火; 和组件	BOILER; FIRE TUBE AND COMPONENTS TYPE,32-SAMSS-021	11368
Static Equipment	600002398	BURNER; SAES-F-01;	燃烧器	BURNER; ANY TYPE,SAES-F-01	11373
Static Equipment	600002481	TANK; FIBER GLASS; 32-SAMSS-002	玻璃钢储罐	TANK; ANY TYPE,ANY FIBER GLASS,32-SAMSS-002	11385
Static Equipment	600002508	FLARE; PROCESSED PLANT; INCLUDING TEMPER	火炬; 工艺类	FLARE; PROCESSED PLANT TYPE,32-SAMSS-022,31-SAMSS-003 32-SAMSS-004,32-SAMSS-011 32-SAMSS-013,34-SAMSS-830 34-SAMSS-711,INCLUDING TEMPERATURE CONTROLS,IGNITERS AND STACK AND BURNPIT WITH ACCESSORIES, FOR FGRS INCLUDES: COMPRESSORS, PRESSURE VESSELS(WATER SEAL DRUMS) OR CONTROL VALVES WITH BUCKING PIN VALVES, BLOWERS AND AIR COOLED HEAT EXCHANGERS. FOR IN-HOUSE HPAAS (HIGH PRESSURE AIR ASSIST SYSTEM) FLARE SMOKELESS APPLICATION INCLUDE: HPAAS FLARE TIP, COMPRESSORS, PRESSURE VESSELS(AIR DRYER AND RECEIVER DRUM), CONTROL VALVES AND HEAT EXCHANGERS.	11390
Static Equipment	600002748	IGNITER	点火器	IGNITER; FLARE TYPE,FLARE	11395
Static Equipment	600009264	JOINT, METAL TO METAL SEAL	接头, 金属对金属密封	COUPLING PIPE; METAL TO METAL (POSITIVE OR NEGATIVE) SEAL MECHANICAL TERMINAL,IN NPS,OY STEEL,MM (IN),PSI SUPPLY, M,GED MLESS UGHT,E URAL FINISH,ASME,ASME,(IN) (IN),ITIVE OR NEGATIVE ITIVE OR NEGATIVE JOINT; METAL TO METAL SEAL MECHANICAL TYPE,CS/SS/ALLOY STEEL,(IN) (IN),ITIVE OR NEGATIVE ITIVE OR NEGATIVE	11403
Static Equipment	600009414	VALVE, SANDWICH, 2 IN. AND UP, ASME CLAS	三明治阀, 2英寸以上, ASME级别	VALVE; GATE, SANDWICH TYPE,SIZE NPS 2 AND UP, STEEL,ASME CLASS 150 AND UP SUPPLY,FLANGE END CONN,04-SAMSS-035,04-SAMSS-048	11409
Static Equipment	600009454	VALVE,CHECK,14 IN &UP,CAST OR DUCTILE IR	止回阀; 铸铁 14英寸及以上	VALVE CHECK; SIZE 14 IN. AND UP,ANY SUPPLY,CAST OR DUCTILE IRON BODY,SWING,FLANGED, LUG OR WAFER END CONN,04-SAMSS-035,04-SAMSS-048	11415
Static Equipment	6000011206	SKID; FILTRATION SYSTEM	过滤系统撬	SKID; 32-SAMSS-038 (IF SKID),DESIGN,ASSEMBLY AND DESIGN OF FILTRATION SYSTEM (HYDROCARBON SERVICE) OIL /GAS/WATER STREAM	11421
Static Equipment	6000011955	SKID; THERMAL OXIDIZER	热氧化器撬	FURNACE; BUSTION CHAMBER FABRICATORS RMAL OXIDIZER EQUIPMENT TYPE,INCLUDING BURNER	11427
Static Equipment	6000013010	VALVE; GATE, GLOBE&CHECK, CRYOGENIC	阀门; 闸、截至、止回, 深冷用	VALVE GATE; GLOBE&CHECK, CRYOGENIC TYPE,SIZE ANY SIZE,ANY RATING SUPPLY,ANY BODY,04-SAMSS-035,04-SAMSS-048 04-SAMSS-001,04-SAMSS-002 04-SAMSS-005,AS APPLICABLE FOR THE VALVE TYPE, INCLUDING THE ADDITIONAL REQUIREMENTS IN THE CRYOGENIC APPENDICES.	11435
Static Equipment	6000013091	TUBE; CATALYST, ASSEMBLIES	炉管; 催化, 组装式	TUBE; CATALYST ASSEMBLIES TYPE,CENTRIFUGAL CAST. HYDROCARBON	11442
Static Equipment	6000013742	VALVE; BALL; DOUBLE ISOLATION TWIN	球阀; 双球	VALVE, BALL; SIZE UP TO 24 IN,ANSI CL 150 AND UP SUPPLY,FLANGED OR BUTTWELD END CONN,ANY BODY,STYLE SPLIT BODY,TRUNNION SUPPORTED SUPPORT,04-SAMSS-048,04-SAMSS-035 04-SAMSS-051,DOUBLE ISOLATION TWIN BALL WITH OR WITHOUT ACTUATOR	11449
Static Equipment	6000014202	FITTING; PIPE; CUNI;ALL TYPES;EEMUA 146	管件; 铜镍合金 符合EEMUA 146	FITTING; PIPE; EEMUA 234,CUNI PIPE FITTINGS, ALL TYPES, INCLUDING ELBOWS, TEES, REDUCERS, CAPS, COUPLING, BRANCH CONNECTION, BW OR SW OR THREADED AS PER EEMUA 234. NON-HYDROCARBON UTILITY.	11455
Static Equipment	6000014491	VALVE; NPS 2 TO 20, COMPOSITE MATERIAL	阀门; NPS 2至20英寸, 复合材料	VALVE; BUTTERFLY, BALL OR CHECK TYPE,SIZE NPS 2 THRU 20,ASME CLASS 150 & 300 SUPPLY,FLANGED END CONN,COMPOSITE (NON-METALLIC) BODY	11463
Static Equipment	6000014971	COUPLER;LPG LOADING,INCLUDE VAPOR	连接器; LPG加载用	COUPLER; LPG LOADING TYPE,SIZE ALL SIZES,HARD PIPE TERMINAL,INCLUDE VAPOR AND BREAKAWAY COUPLERS,CONTACT CSD FOR DETAILS	11471
Static Equipment	6000015021	VALVE; CHECK; API 6A 10,000; SWING	止回阀; 符合API 6A 10,000磅级	VALVE CHECK; SIZE 1-13/16 IN AND UP, API 10000 SUPPLY,STEEL BODY,SWING,FALNGED HUBBED OR BUTT-WELD END CONN,04-SAMSS-055,API 6A	11478
Static Equipment	6000015600	VAPOR RECOVERY UNIT (VRU)	蒸气回收装置 (VRU)	UNIT; VAPOR RECOVERY UNIT TYPE,32-SAMSS-004,32-SAMSS-019 API-672,API-681 ASME B73.1 OR ISO 2858,ISO SAES-G-005,SAES-K-101 ASHRAE 90.1 EER,VAPOR RECOVERY UNITS (VRU) IS A PROCESS UNIT/MODULE THAT RECOVERS VOLATILE ORGANIC COMPOUNDS, VOCs, OR VENT GASES SUCH AS METHANE, ETHANE, PROPANE AND CARBON DIOXIDE TO AVOID VENTING TO ATMOSPHERE OR FLARE. IT IS USED TO RECOVER VAPORS THAT RESULT FROM LOADING OF PETROLEUM AND PETROCHEMICAL PRODUCTS AND TRANSFER OF EVAPORATIVE HYDROCARBONS SUCH AS GASOLINE, NAPHTHA, AROMATICS, FUEL AND ALCOHOL	11486
Static Equipment	6000015604	VALVE;CHOKE;MS;UP TO 6 IN,2K-SKPS,API6A	节流阀; 最大6英寸, 2000-5000磅级, 符合API6A	VALVE CHOKE; ANY BODY,UP TO 6 INCH MAX ORIFICE,PR 2000-5000 PSI SUPPLY,FLANGED HUBBED OR BUTTWELD END CONN,ANY BODY, MULTISTAGE TRIM,04-SAMSS-055,API 6A	11492
Static Equipment	6000017141	INLINE MIXING SKID;	管路混合撬;	SKID; VALVE/SPOOL TYPE,SAES-A-010,01-SAMSS-010 04-SAMSS-01/02/048,SAES-W-0-ANSI B31.3,SAES-J-700,INLINE HIGH EFFICIENCY MIXER PACKAGE, ADJUSTABLE OR STATIC, TYPICALLY HAS PIPE & FITTINGS, INJECTION CONE AND INJECTION PIPE, SPOOL, INJECTION QUILL, HOUSING, INTERNAL MIXING PARTS COULD BE FOR SOUR OR NON-SOUR SERVICE 8-32 NPS PRODUCT RANGE, ANSI FLANGE 150# TO 900#. FOR MIXING OIL WITH WATER OR CHEMICALS. FABRICATION WITH APPROVED MANUFACTURER	11500

Material Sourcing Gaps - China 2021

Static Equipment	6000017431	UNIT, CENTRIFUGE PACKAGE (VERTICAL OR HO	离心机组	UNIT; CENTRIFUGE PACKAGE (VERTICAL OR HORIZONTAL) TYPE,DEVICE/PACKAGE USED TO SEPARATE TWO OR THREE PHASES FROM EACH OTHER BY CENTRIFUGAL FORCE OR ROTATION. APPLIES SEDIMENTATION PRINCIPLE TO SEPARATE HEAVIER/DENSER SUBSTANCE/PARTICLE FROM LESS DENSE FLUIDSEPARATION OF WATER FROM OIL, OIL FROM WATER, SOLIDS FROM OIL, SOLIDS FROM LIQUIDS (WATER AND GLYCOL) OR THREE PHASE SEPARATION (SOLIDS, WATER, OIL)	11508
Static Equipment	6000017260	SKID, NITROGEN; PRESSURE SWING ADSORPTIO	氮气发生器; 变压吸附	SKID; NITROGEN ADSORPTION (PSA) SSURE SWING TYPE,32-SAMSS-038,NITROGEN GENERATION UNIT, PSA (PRESSURE SWING ADSORPTION) TYPE. USES ADSORBENT SUCH AS CARBON MOLECULAR SIEVE. MORE THAN 95% VOLUME PURITY NITROGEN	11517
Static Equipment	6000017340	VALVE, BALL; SIZE UP TO NPS 12 INCH,ANY SUPPLY	球阀; 最大NPS 12英寸	VALVE, BALL; SIZE UP TO NPS 12 INCH,ANY SUPPLY,ANY END CONN,DUCTILE OR CAST IRON BODY,04-SAMSS-035 04-SAMSS-048 AWWA OR OTHER EQUIVALENT,2 OR 3 WAY,WITH OR WITHOUT ACTUATOR	12594
Static Equipment	6000000308	VALVE; PLUG; LUBRICATED	润滑旋塞阀	VALVE PLUG; LUBRICATED TYPE,SIZE ANY SIZE,ANY PRESSURE RATING SUPPLY,ANY END CONN,STEEL BODY,04-SAMSS-035,04-SAMSS-048 04-SAMSS-053,04-SAMSS-055 ASME B16.34,API 599 API 6A,WITH OR WITHOUT ACTUATOR,ASME CLASS 150 AND UP, API 2000 TRHU 5000.	12603
Static Equipment	6000017570	BURNER, BOILER, STEAM GENERATOR	燃烧器, 锅炉, 蒸汽发生器	BURNER; BOILER, STEAM GENERATOR TYPE,SIZE ANY,ANY SHAPE,ANY	12612